

# Accent

Track mounted adjustable LED spotlight for accent lighting



Direct D3 Surface Mount



Accent, black



Accent on Surface Adapter

## Optics

- Nominal 1000 and 2000 lumens (10W and 20W)
- 3000K and 4000K colour temperatures
- Ra >80
- Narrow, medium and wide optics (20°, 26° and 36° beam angles)
- 60,000 hours to L70B10

## Body

- For use with Whitecroft Direct D3 track (3 circuit and Dali dimming)
- Adapter is compatible with:
  - Global Pro Trac - non DALI
  - Global Pro Pulse - DALI
- IP20
- Extruded aluminium body
- White RAL 9016 or black RAL 9005 finish
- Fixed output and DALI dimming options
- Electrical Class 1
- >0.9 power factor
- Suitable for ambient temperatures -25 to +25°C
- Stand-alone emergency available (see Direct D3 Track web page)
- Surface mounting adapter for use without track

# Order codes

## 4000K

| Version                          | Fixed Output, white | Fixed Output, black | LL/CW | L70 |
|----------------------------------|---------------------|---------------------|-------|-----|
| 1113 lumen, 10.1W, narrow, 4000K | UAH14KWN            | UAH14KBN            | 110.2 | 60k |
| 1171 lumen, 10.1W, medium, 4000K | UAH14KWM            | UAH14KBM            | 115.9 | 60k |
| 1054 lumen, 10.1W, wide, 4000K   | UAH14KWW            | UAH14KBW            | 104.4 | 60k |
| 1981 lumen, 20.6W, narrow, 4000K | UAH24KWN            | UAH24KBN            | 96.2  | 60k |
| 2086 lumen, 20.6W, medium, 4000K | UAH24KWM            | UAH24KBM            | 101.3 | 60k |
| 1877 lumen, 20.6W, wide, 4000K   | UAH24KWW            | UAH24KBW            | 91.1  | 60k |

## 3000K

| Version                          | Fixed Output, white | Fixed Output, black | LL/CW | L70 |
|----------------------------------|---------------------|---------------------|-------|-----|
| 1053 lumen, 10.1W, narrow, 3000K | UAH13KWN            | UAH13KBN            | 104.3 | 60k |
| 1109 lumen, 10.1W, medium, 3000K | UAH13KWM            | UAH13KBM            | 109.8 | 60k |
| 998 lumen, 10.1W, wide, 3000K    | UAH13KWW            | UAH13KBW            | 98.8  | 60k |
| 1879 lumen, 20.6W, narrow, 3000K | UAH23KWN            | UAH23KBN            | 91.2  | 60k |
| 1978 lumen, 20.6W, medium, 3000K | UAH23KWM            | UAH23KBM            | 96    | 60k |
| 1780 lumen, 20.6W, wide, 3000K   | UAH23KWW            | UAH23KBW            | 86.4  | 60k |

## Options

| Title        | Code                            |
|--------------|---------------------------------|
| DALI dimming | Change 'H' to 'Y' i.e. UAY14KWN |


## Accessories/Attachments

| Title  | Code   |
|--|--------|
| Surface adapter, white                                   | DDCLGW |
| Surface adapter, black                                   | DDCLGB |
| For compatible 3 circuit and Dali track, see 'Direct D3' |        |

# LED Performance


|               |          |                    |
|---------------|----------|--------------------|
| Colour Temp   | RA (CRI) | Colour consistency |
| 3000K / 4000K | 80       | MacAdam 3 SDCM     |

## Dimensions




| VERSION    | L   | W   | H   | KG  |
|------------|-----|-----|-----|-----|
| 1000 lumen | 122 | 130 | 145 | 0.9 |
| 1750 lumen | 122 | 130 | 145 | 0.9 |


## Photometric Performance



4000K 1683 lm  
22W Narrow  
LOR = 100%



4000K 1965 lm  
22W Medium  
LOR = 100%



4000K 1595 lm  
22W Wide  
LOR = 100%

## To Specify

Track mounted LED spotlight with integrated driver, fixed output or DALI dimming. Extruded aluminium body with choice of narrow, medium or wide distribution with fully adjustable swivel and tilt - as Whitecroft Lighting ACCENT.

## Application images

