


# Avenue Micro Suspended



Suspended continuous or standalone slim linear feature luminaire



## Overview

Avenue Micro offers unparalleled flexibility for linear lighting in any application. Lines of unbroken LED light bringing buildings to life.

---

## Optics

- Luminaire available as 100% downlight or 70/30% down/uplight
- Two lengths with four light outputs (4000K):
  - 1122mm - 1322 lumens (12.9W) - continuous or standalone
  - 1122mm with uplight - 1629 lumens (15.1W) - continuous or standalone
  - 2244mm - 2643 lumens (25.8W) - continuous only
  - 2244mm with uplight - 3258 lumens (30.7W) - continuous only
- Micropolymer diffuser for uniform light diffusion
- Tp(a) rated diffuser
- 3000K or 4000K LED

# Body

- Slim-line linear LED suspended lighting system
- Available in continuous or standalone
- Continuous luminaires are supplied complete with continuous mounting kit and brackets and are through-wired as standard
- IP20
- When continuously mounting, LEDs run the entire length of each light engine, eliminating dark spots and shadows
- Slim extruded aluminium body finished in textured white or textured silver
- RAL Colour: Silver RAL9006 or White RAL9003
- End cap kit to be ordered separately
- One suspension wire (2m long) included with each luminaire and each end cap kit
- Avenue Micro Recessed also available, see dedicated web page
- Available with integral emergency:
  - 3 hour self contained
  - 3 hour addressable test
- Emergency outputs:
  - Downlight only - 370 lumens
  - Up/downlight - 390 lumens

## Order codes

### Continuous, Textured Silver

			B50		
Continuous, Textured Silver	Fixed Output	LL/CW	L70	L80	L90
1122mm - 1322 lumens (12.9W)	AMSH2S	102	60K	60K	50K
1122mm - 1629 lumens with uplight (15.1W)	AMSUPH2S	107	60K	60K	50K
2244mm - 2643 lumens (25.8W)	AMSH3S	102	60K	60K	50K
2244mm - 3258 lumens with uplight (30.7W)	AMSUPH3S	106	60K	60K	50K

Note: Luminaire codes AMSY3 and AMSUPY3 have 2 drivers and require 2 DALI addresses

### Standalone, Textured Silver

			B50		
Standalone, Textured Silver	Fixed Output	LL/CW	L70	L80	L90
1122mm - 1322 lumens (12.9W)	AMSSTH2S	102	60K	60K	50K
1122mm - 1629 lumens with uplight (15.1W)	AMSSTUPH2S	107	60K	60K	50K

## Accessories

End cap kit (pair), textured silver	AMSECS
-------------------------------------	--------


## Options

DALI	Replace H with Y	i.e AMSY2S
Textured White	Replace S with W	i.e AMSH2W
3000K	Add '3' after 2 or 3	i.e AMSH23S
3 hour emergency	Add suffix 'EM'	i.e AMSH2SEM
3 hour COMEPE emergency	Add suffix 'EP'	i.e AMSH2SEP

## LED Performance


Colour Temp	RA (CRI)	Colour consistency
4000K	>80	MacAdam 3 SDCM

## Dimensions




VERSION	L	W	H	KG
1322lm	1122	46	104	2.6
1629lm (with uplight)	1122	46	104	3.1
2643lm	2244	46	104	5.3
3258lm (with uplight)	2244	46	104	6.1

# Photometric Performance



4000K  
Up/Downlight  
15.1W LED 1629  
Lumens  
LOR = 100.0%  
SHR MAX = 1.48

---



4000K 25.8W LED  
2643 Lumens  
LOR = 100.0%  
SHR MAX = 1.49

---

---

## To Specify

Slim-line suspended linear LED luminaire for continuous or standalone applications. Micropolymer Tp(a) rated diffuser – as Whitecroft Lighting AVENUE MICRO SUSPENDED.

---