



Whitecroft Vitality - Cascade Flex Cascade Flex Tunable White Cascade Flex

Part Code Logic

Part Code Logic



Type	Optics	E Light	Integral Controls	Drivers	Nominal Output Lumens	CCT / Ra	Ceiling Type	Emergency
Cascade Flex 600 x 600mm (C6)	Pod (P) Diffuser (D)	-	N/A () Organic Response (BRG)	FO (H) DALI (Y) Tunable (TE)	2300 (1) 3300 (2) 4100 (3) 5100 (4)	4000K, Ra80 (4K8) 3000K, Ra80 (3K8) Tunable White ()	Exposed Tee (XT) Spring Tee (ST)	EM (EM) COMEPS (EP)
Cascade Flex 1200 x 300mm (C12)	Pod (P)	-	N/A () Organic Response (RG)	FO (H) DALI (Y) Tunable (TE)	3300 (2) 4100 (3)	4000K, Ra80 (4K8) 3000K, Ra80 (3K8) Tunable White ()	SAS 330 ()	EM (EM) COMEPS (EP)
Whitcroft Vitality - Cascade Flex 600 x 600mm (C6)	Pod (P)	E-light (E)	N/A () Organic Response (BRG)	DALI (Y)	3300 (2) 4100 (3)	4000K, Ra80 (4K8) 3000K, Ra80 (3K8) 4000K, Ra90 (4K9) 3000K, Ra90 (3K9)	Exposed Tee (XT) Spring Tee (ST)	EM - Lithium (EM) COMEPS - Lithium (EP)
Whitcroft Vitality - Cascade Flex 1200 x 300mm (C12)	Pod (P)	E-light (E)	N/A () Organic Response (RG)	DALI (Y)	3300 (2) 4100 (3)	4000K, Ra80 (4K8) 3000K, Ra80 (3K8) 4000K, Ra90 (4K9) 3000K, Ra90 (3K9)	SAS 330 ()	EM - Lithium (EM) COMEPS - Lithium (EP)

Examples: C6PEBRGY34K8XTEM – Cascade Flex Vitality, 600sq, Pod, e-light, Organic Response, DALI, 4100 lumen, 4000K, Ra80, Exposed Tee, 3 hour emergency
 C12PH24K8 - Cascade Flex, 1200x300mm, Pod, fixed output, 3300 lumens, 4000K, Ra80, SAS 330

Notes:

- Tunable White 4100 lumens only, no emergency
- 5100 lumens with diffuser only
- E-light and Lithium batteries as standard for Vitality versions