Convex

Low profile emergency bulkhead











Convex Blade

Optics

Convex 65

- IP65
- LED emergency bulkhead for wall or ceiling mounting
- Polycarbonate body finished white with clear polycarbonate lens
- 16 x low energy LEDs producing 120 lumens
- Self adhesive legends for application to bulkhead available in up/down, left and right (supplied separately)
- Legends have a viewing distance of up to 20m

Convex Blade

- IP65
- · LED emergency luminaire with slotted diffuser for integrating hanging legend 'blade' (supplied separately)
- Polycarbonate body finished white with clear polycarbonate lens
- Choice of up, down and right/left legends
- Polycarbonate legend panels supplied separately
- Legends supplied in accordance with BS 5266-1 2011 (ISO7010)
- Legends have a viewing distance of up to 20m

Body

- Low voltage LED emergency bulkhead
- High temperature Ni-Cd battery with constant current charger and LED charge indicator
- BESA rear cable entry
- Ambient 0 25°C
- 3 hour maintained (can be wired as non-maintained) or mains voltage
- Power consumption:
 - o 6W maintained
 - · 4W non maintained
 - o 2W mains

Order codes

Convex 65

Convex 65	3hr Emergency	LL/CW
120 Lumens (2W) mains voltage	CXMAINS	31
120 Lumens (2W) 3 hour maintained	CXM3	31

Convex Blade

Convex Blade	3hr Emergency	LL/CW
2W mains voltage	CXBMAINS	31
6W 3hr maintained	CXBM3	

Convex 65 Legends*

Convex 65 Legends*	3hr Emergency		
Right Legend - Single Sided Adhesive	CX7010R		
Down Legend - Single Sided Adhesive	CX7010D		
Up Legend - Single Sided Adhesive	CX7010U		
Left Legend - Single Sided Adhesive	CX7010L		

Convex Blade Legends*

Convex Blade Legends*	3hr Emergency		
Up Legend - Double Sided	CXB7010U		
Right/Left Legend - Double Sided	CXB7010RL		
Down Legend - Double Sided	CXB7010D		

Options

COMEPS** Add suffix /EP i.e CXM3/EP

Dimensions

VERSION	L	W	Н	H1	KG	
Convex	240	130	50		1	
Convex Blade	240	130		100	1.4	

To Specify

Convex 65

LED IP65, mains or 3 hour self-contained maintained emergency ceiling or wall mounted luminaire with rigid polycarbonate body and clear polycarbonate lens. Self adhesive legends available separately. High temperature Ni-Cd battery with constant current charger and LED charge indicator - as Whitecroft Lighting CONVEX 65

Convex Blade

LED IP65, mains or 3 hour self-contained maintained emergency ceiling mounted luminaire with rigid polycarbonate body with clear, slotted polycarbonate lens for integration of opal polycarbonate green exit legend. High temperature Ni-Cd battery with constant current charger and LED charge indicator - as Whitecroft Lighting CONVEX BLADE

^{*} Legends to be ordered separately

^{**} COMEPS can be wired as Easytest if required