Kolo IP65 Hood

IP65 LED surface mounted amenity luminaire with hood













Kolo IP65 Hood - Silver

Overview

Kolo brings style and efficiency to any application. With a host of optional attachments to add visual interest, Kolo is the optimum lighting solution.

Optics

- Light output options:
 - o 1008 lumen, 14W
- Polycarbonate opal diffuser
- 'Cool' white 4000K colour temperature as standard
- 3000K LED available
- Emergency output: 200 lumen


Body

- Surface mounted
- 400mm diameter in cast aluminium with injection moulded base
- IP65
- · Finished in silver or black
- Choice of integrated emergency options:
 - o 3 hour emergency
 - COMEPS
- Emergency variants supplied with Lithium Iron Phosphate (LiFePO4) batteries
- Trim ring supplied as standard

LED Performance

Colour Temp	RA (CRI)	Colour consistency
4000K	>80	MacAdam 3 SDCM

Dimensions



VERSION	W	KG	KG(EM)	Ø	
400mm ø	95	4	4.5	400	

Photometric Performance



14W LED 1008 lumens LOR = 100%

To Specify

Surface mounted circular IP65 LED bulkhead luminaire in 400mm diameter. Polycarbonate opal diffuser. Supplied with trim ring – as Whitecroft Lighting KOLO IP65 HOOD