

Egress 65

IP65 recessed emergency luminaire

Whitecroft
lighting



Optics

- Fully recessed high grade polycarbonate body mounted in ceiling tile with winged fixings adjustable from below with white lip trim, recess depth 85mm
- Low voltage LED recessed emergency luminaire
- High temperature Ni-Cd battery with constant current charger and LED charge indicator
- Cable entry locations at rear
- Ambient 0 – 25°C

Body

- IP65
- Polycarbonate body finished white with clear polycarbonate lens
- 16 x low energy LEDs producing 168.8 lumens
- 3 hour maintained or mains voltage versions
- Also available with "EW" Routefinder Wireless for addressable emergency testing without the need for a 2 core communication cable
- Power consumption:
 - 11.5W maintained
 - 5W mains

Order codes

Egress 65

Egress 65	3hr Emergency	230V Mains	COMEPS *	Wireless Routefinder
168.8 lumens (11.5W) 3hr maintained	EG65M3	N/A	EG65M3/EP	EG65M3/EW
168.8 lumens (5W) mains voltage	N/A	EG65MAINS	N/A	N/A

* COMEPS can be wired as Easytest if required

Dimensions

VERSION	L	W	H	KG	Cut Aperture
Egress 65	420	165	85	1.3	390x135

To Specify

LED IP65, mains or 3 hour self-contained maintained emergency recessed luminaire with rigid polycarbonate body and clear polycarbonate lens. High temperature Ni-Cd battery with constant current charger and LED charge indicator – as Whitecroft Lighting EGRESS 65