

asymmetric wallwasher

Display: Compact fluorescent recessed and surface wallwasher

APPLICATION

- Retail applications
- Shops
- Shelving
- Walls
- Displays to vertical surfaces

SPECIFICATION

- Lamp options:
 - 1 x 55W TC-L
 - 2 x 55W TC-L
- Universal body for recessed or surface mount
- Recessed body – exposed tee 25mm or 15mm
- Body:
 - fabricated steel
 - polyester powder paint finish RAL 9010
- BESA fixings at rear
- High frequency gear as standard
- Fused terminal block
- Supplied less lamps
- Reflector:
 - lay-in asymmetric
 - semi-specular, low glare
- Recommended spacing: 750mm from approximate vertical surface and on 1.8m centre for even illumination




Recessed mount

PHOTOMETRY

Asymmetric Wallwasher COMPACT FLUORESCENT 1 x 55W TC-L Lamp



• LOR = 53.5%



DIMENSIONS



	A	B	C	D	E
Single lamp	594	80	200	500	110
Twin lamp	1194	80	200	1100	110

LAMP PERFORMANCE MATRIX

WATTAGE	IL@25°C	LAMP LIFE
1 x 55W TC-L	4800	12,000

ORDER CODES – ASYMMETRIC WALLWASHER

COMPACT FLUORESCENT WALLWASHER

SUPPLIED LESS LAMPS	LENGTH MM	GEAR	LUMINAIRE
1 x 55W TC-L	600	High frequency	ASYU155S
2 x 55W TC-L	1200		ASYU255S

To specify state:

Universal fully recessed/surface compact fluorescent asymmetric luminaire. Semi-specular parabolic low glare louvre – as Whitecroft Lighting ASYMMETRIC WALLWASHER

QuickLink

ASYW

Go