

avenue micro recessed

recessed continuous or
standalone slim linear
feature LED luminaire



Optics

- Product available in three lengths with three light outputs;
 - 600mm* - 600 lumens (8W)
 - 1200mm* - 1200 lumens (15W)
 - 2400mm* - 2500 lumens (30W)
- Micropolymer diffuser for uniform light diffusion
- Diffusers clip in to enable the product to be recessed into the wall as well as the ceiling
- 4000K 'cool' white LEDs


*Lengths are nominal. For exact lengths please refer to the dimensions section

Body

- Recessed linear system for ceiling or wall mounting
- Available as continuous or standalone
- Continuous luminaires are supplied complete with continuous mounting kit and brackets and are through-wired as standard
- IP40 from below (IP20 from behind)
- LEDs run the entire length of each luminaire, eliminating dark spots and shadows
- Slim extruded aluminium body finished in textured white
- End cap kit to be ordered separately
- Suitable for Exposed T and plasterboard ceilings, and wall mounting
- Avenue Micro Suspended also available. See Whitecroft website



Dimensions



Version	L	W	H	KG
600lm	564	58.4	65.6	1.3
1200lm	1122	58.4	65.6	2.3
2500lm	2244	58.4	65.6	4.6

Order Codes

Continuous

600 lumens (8W)
1200 lumens (15W)
2500 lumens (30W)

Fixed output

AMRH1W
AMRH2W
AMRH3W

Standalone

1200 lumens (15W)

AMRSTH2W

Accessories


End cap kit, (pair)

AMRECW


Options

DALI Replace H with Y i.e. AMRY1W

Photometric Performance



8W LED
600 lumens
• LOR = 100%
• SHR MAX = 1.49



15W LED
1200 lumens
• LOR = 100%
• SHR MAX = 1.49

Utilisation Factors UF(F)

Room Reflectance			Room Index		
C	W	F	1.00	3.00	5.00
0.70	0.50	0.20	0.69	0.97	1.04

Utilisation Factors UF(F)

Room Reflectance			Room Index		
C	W	F	1.00	3.00	5.00
0.70	0.50	0.20	0.69	0.97	1.04

LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	≥ 80	L ₈₀ (50,000hrs)	MacAdam 3 SDCM

Ceiling Integration

Refer to common ceiling compatibility matrix – see Whitecroft website

Exposed T Grids

T15/T25 Pull up

Plasterboard

Prepared aperture (brackets are included with body)

To Specify

Slim-line recessed linear LED luminaire for continuous or standalone application in ceilings or walls. Micropolymer diffuser – as Whitecroft Lighting AVENUE MICRO RECESSED.