

broadspread asymmetric

asymmetric luminaire ideal for corridors

> weblink > **BASM**

Optics

- Asymmetric cross blade louvre
- Lamp options:
 - 1 x 54W T5
 - additional 7W TC-S night light option for healthcare applications

Body

- Steel body finished white
- Designed to fit exposed T15, T25 or plasterboard ceilings



ORDER CODES

Broadspread Asymmetric	HF Gear	3 hr Emergency
T5 1 x 54W	BASMH154	BASMH154EMIN
T5 1 x 54W with Nightlight	BASMH154NL	BASMH154NLEMIN

Options


DALI DIMMING	Replace H with Y in order code	i.e. BASM Y 154
DSI DIMMING	Replace H with D in order code	i.e. BASM D 154
SWITCH DIMMING	Replace H with X in order code	i.e. BASM X 154
EASYTEST	Add suffix /ET to order code	i.e. BASMH154/ ET
COMET	Add suffix /CT to order code	i.e. BASMH154/ CT
PREPARED APERTURE INSTALLATION KIT		BASYSBKIT

LAMP PERFORMANCE

Wattage	IL@25°C	Lamp Life
1 x 54W T5	4450	24,000hrs

PERFORMANCE GUIDE


Lamps	Illuminance	Spacing
1 x 54W T5	180 lux	3.6m



Maintenance: 0.8	Ceiling Height: 2.7m
Reflectance: 70/50/20	Working Plane: 0.0m




DIMENSIONS



Version	L	W	H	Prepared Aperture	KG	KG
Exposed T/Plasterboard	1197	197	80	175 x 1175 ⁻³ ₊₃	3.5	4.5

PHOTOMETRIC PERFORMANCE



- 1 x 54W T5
- LOR = 65.4%
 - SHR MAX = 1.66

Utilisation Factors UF(F)

Room Reflectance			Room Index		
C	W	F	1.00	3.00	5.00
0.70	0.50	0.20	0.51	0.67	0.70

CEILING INTEGRATION

Refer to common ceiling compatibility matrix – See page 310

Exposed T Grids

- T25 Lay in
- T15 Lay in
- T15/T25 Pull up (Installation kit required)

Plasterboard

Prepared aperture (Installation kit required)

TO SPECIFY

Asymmetric corridor T5 luminaire, with 7W TC-S night light option. Rigid and jointed steel body and screwless steel front frame, finished white. Designed to fit both exposed T-bar or plasterboard ceilings & including close wall mounting up to 40mm. Positively retained asymmetric cross-blade louvre – as Whitecroft Lighting BROADSPREAD ASYMMETRIC