





Optics

- Lamp options:
 - 35W CDMT
 - 50W SON-T
 - 42W TC-T
- Clear polycarbonate cover with stainless louvre or opal polycarbonate diffuser

Body

- IP65 ingress protection
- Tubular steel body and top cap, available in black powder coated finish or stainless steel
- Round or square head options
- Flange or root mount options
- Head and bollard supplied separately. Bollard section contains gear

Order Codes

Head (Round)	Black	Stainless Steel
Opal Diffuser	BRKHEADOBR	BRKHEADOSR
Stainless Steel Louvre	BRKHEADLBR	BRKHEADLSR

Head Options		
SQUARE HEAD	Replace R with Q	i.e. BRKHEADOBQ

Bollard Base (Root Mounted)	Black	Stainless Steel
35W CDMT	BRK35HBR	BRK35HSR
50W SON-T	BRK50SBR	BRK50SSR
42W TC-T	BRK42FBR	BRK42FSR

Base Options		
FLANGE MOUNT*	Replace R with F	i.e. BRK70HBF

*Flange mount not available in stainless steel bollard bases
Note: Complete bollard consists of bollard base with optic and head which contains diffuser/louvre. Both must be ordered for complete unit.

Round head



Stainless steel louvre and clear polycarbonate

Square head




Opal diffuser

Dimensions

Version Round Head	Version Square Head
W 177	W 177
H 976	H 930
KG 9.0	KG 9.0
Version Root mount	Version Flange mount
H 130	W 191
H1 480	L 191
KG 7.0	

Photometric Performance



1 x 35W HQI-E
Opal Diffuser

Lamp Performance

Wattage	IL@25°C	Lamp Life
1 x 35W CDMT	3300	12,000hrs
1 x 50W SON-T	4400	30,000hrs
1 x 42W TC-T	3200	13,000hrs

To Specify

IP65 bollard in stainless steel or black powder coated steel. With opal polycarbonate diffuser or stainless steel louvre with clear polycarbonate cover – as Whitecroft Lighting BROADWALK