

Optics

- Lamp options:
 - 35W CDMT
 - 50W SON-E
 - 42W TC-T
- Clear polycarbonate cover with stainless louvre or opal polycarbonate diffuser

Body

- IP65 ingress protection
- Tubular steel body and top cap, available in black powder coated finish or stainless steel
- Round or square head options
- Flange or root mount options
- Head and bollard supplied separately. Bollard section contains gear

Order Codes

Head (Round)	Black	Stainless Steel
Opal Diffuser	BRKHEADOBR	BRKHEADOSR
Stainless Steel Louvre	BRKHEADLBR	BRKHEADLSR

Head Options		
SQUARE HEAD	Replace R with Q	i.e. BRKHEADOBQ

Bollard Base (Root Mounted)	Black	Stainless Steel
35W CDMT	BRK35HBR	BRK35HSR
50W SON-E	BRK50SBR	BRK50SSR
42W TC-T	BRK42FBR	BRK42FSR

Base Options		
FLANGE MOUNT*	Replace R with F	i.e. BRK35HBF

*Flange mount not available in stainless steel bollard bases


Note: Complete bollard consists of bollard base with optic and head which contains diffuser/louvre. Both must be ordered for complete unit.



Dimensions

Version	W	H	KG		Version	W	H	KG
Round Head	177	976	9.0		Square Head	177	930	9.0
Version	H ₂	H ₁	KG		Version	W	L	
Root mount	610	455	7.0		Flange mount	191	191	

Photometric Performance



Lamp Performance

Wattage	IL@25°C	Lamp Life
1 x 35W CDMT	3300	12,000hrs
1 x 50W SON-E	3500	28,000hrs
1 x 42W TC-T	3200	13,000hrs

To Specify

IP65 bollard in stainless steel or black powder coated steel. With opal polycarbonate diffuser or stainless steel louvre with clear polycarbonate cover – as Whitecroft Lighting BROADWALK