

broadwalk

IP55 amenity bollard

> weblink > **BRK**

Optics

- Lamp options:
 - 70W SON/HQI-E
 - 42W TC-T
- Clear polycarbonate cover with stainless louvre or opal polycarbonate diffuser

Body

- IP55 ingress protection
- Tubular steel body and top cap, available in black powder coated finish or stainless steel
- Round or square head options
- Flange or root mount options
- Head and bollard supplied separately. Bollard section contains gear



ORDER CODES

Head (Round)	Black	Stainless Steel
Opal Diffuser	BRKHEADOBR	BRKHEADOSR
Stainless Steel Louvre	BRKHEADLBR	BRKHEADLSR

Head Options

SQUARE HEAD	Replace R with Q in order code	i.e. BRKHEADOBQ
-------------	---------------------------------------	------------------------


Bollard Base (Root Mounted)	Black	Stainless Steel
70W HQI-E	BRK70HBR	BRK70HSR
70W SON-E	BRK70SBR	BRK70SSR
42W TC-T	BRK42FBR	BRK42FSR

Base Options

FLANGE MOUNT	Replace R with F in order code	i.e. BRK70HBF
--------------	---------------------------------------	----------------------

Note: Complete bollard consists of bollard base with optic and head which contains diffuser/louvre. Both must be ordered for complete unit.

PHOTOMETRIC PERFORMANCE



1 x 70W HQI-E
Opal Diffuser

Round head




Stainless steel
louvre and clear
polycarbonate

Square head




Opal diffuser


DIMENSIONS



Version	W	H	KG
Round Head	177	976	9.0



Version	W	H	KG
Square Head	177	930	9.0



Version	H	H ₁	KG
Root mount	130	480	7.0



Version	W	L
Flange mount	191	191

LAMP PERFORMANCE

Wattage	IL@25°C	Lamp Life
1 x 70W SON-E	5600	18,000hrs
1 x 70W HQI-E	6000	20,000hrs
1 x 42W TC-T	3200	12,000hrs

TO SPECIFY

IP55 bollard in stainless steel or black powder coated steel. With opal polycarbonate diffuser or stainless steel louvre with clear polycarbonate cover – as Whitecroft Lighting BROADWALK

