

broadwalk L180

LED 180 degree bollard
for outdoor applications




Optics

- Light output options:
 - 438 lumens, 4000K, 11.5W (600 & 1100mm high versions)
 - 1460 lumens, 4000K, 29W (2400mm high version)
- 180 degree distribution
- UV stabilised polycarbonate opal diffuser

Body

- Die cast aluminium
- Coated for corrosion and saline environment resistance
- IP66 IK08 rated protection
- Finished in Graphite Grey or Silver
- Supplied with plug and socket and fixing bolts
- Suitable for ambient temperatures between -30°C to +4 0°C
- Flange plate mounted



Order Codes

Broadwalk L180

600mm high

1100mm high

2400mm high

BLF1814KG

BLF1824KG

BLF1834KG


Options

SILVER

Replace G with S

i.e. BLF1814KS

Dimensions




Version	L	W	H	L1	L2	KG
600mm high	413	323	600	300	220	6.2
1100mm high	413	323	1100	300	220	8.2
2400mm high	413	323	2400	300	220	13.0

LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000 K	≥ 70	L ₇₀ (40,000hrs)	MacAdam 4 SDCM

Photometric Performance



11.5W 438 lumen
• LOR = 100%

To Specify

IP66 LED bollard with die cast aluminium body in 600, 1100 and 2400mm high options. With 180 degree distribution – as Whitecroft Lighting BROADWALK L180.