

broadwalk RS

IP65 LED amenity bollard



Optics

- 470 – 960 lumens (7.1 – 14.4W)
- 4000K, Ra80 LED
- Clear polycarbonate diffuser
- 360 degree horizontal distribution
- 70% light output at 60,000 hours

Body

- IP65 rated ingress protection
- Tubular reinforced steel body and round head
- Black powder coated polyester coated
- Planted root and flange mounted versions
- Fixed output or Dali dimming control gear
- Supplied as a complete unit including body, head and mounting kit

Order Codes

Fixed output
470 lumen, 7.1W
960 lumen, 14.4W

Planted root
BRLH24KRB
BRLH34KRB

Flange mounted
BRLH24KFB
BRLH34KFB


Options

DALI DIMMING

Change H to Y

i.e. BRLY24KRB

Photometric Performance




14.4W
960 lumen
• LOR = 100%

Dimensions



Version	W	H	KG
Round Head	177	976	9.0



Version	H ₂	H ₁	KG
Root mount	610	455	7.0



Version	W	L
Flange mount	191	191

LED Performance

Colour Temp
4000K

Ra (CRI)
≥ 80

Life Expectancy
L₇₀ (60,000hrs)

Colour Consistency
MacAdam 3 SDCM

To Specify

IP65 LED bollard in black polyester powder coated reinforced steel. With clear polycarbonate diffuser and shielded LED module for control of upward light – as Whitecroft Lighting BROADWALK RS