

broadwalk RS

IP65 LED amenity bollard



Optics

- 470 – 960 lumens (7.1 – 14.4W)
- 4000K, Ra80 LED
- Clear polycarbonate diffuser
- 360 degree horizontal distribution
- 70% light output at 60,000 hours

Body

- IP65 rated ingress protection
- Tubular reinforced steel body and round head
- Choice of stainless steel or black polyester powder coated
- Planted root and flange mounted versions. Flange mounting not available for stainless steel.
- Fixed output or Dali dimming control gear
- Supplied as a complete unit including body, head and mounting kit

Order Codes

Black Polyester Fixed Output	Planted root	Flange mounted
470 lumen, 7.1W	BRLH24KRB	BRLH24KFB
960 lumen, 14.4W	BRLH34KRB	BRLH34KFB


Stainless Steel Fixed Output

470 lumen, 7.1W	BRLH24KRS	–
960 lumen, 14.4W	BRLH34KRS	–

Options

DALI DIMMING	Change H to Y	i.e. BRLY24KRB
--------------	---------------	----------------

Photometric Performance



14.4W
960 lumen
• LOR = 100%




black polyester powder coated




stainless steel

Dimensions



Version	W	H	KG
Round Head	177	976	9.0



Version	H ₂	H ₁	KG
Root mount	610	455	7.0



Version	W	L
Flange mount	191	191

LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	≥ 80	L ₇₀ (60,000hrs)	MacAdam 3 SDCM

To Specify

IP65 LED bollard in stainless steel or black polyester powder coated reinforced steel. With clear polycarbonate diffuser and shielded LED module for control of upward light – as Whitecroft Lighting BROADWALK RS