

Optics

- Lamp options:
 - 2 x 28/54W T5 multi watt control gear
- Circular polycarbonate diffuser
- The solid translucent polycarbonate diffuser guarantees even light dispersion and fades out the shape of the lamp

Body

- Suspended
- Maximum suspension drop 2m
- Extruded plain anodised aluminium body
- Slim anodised aluminium bracket holds a polycarbonate diffuser in which the lamps are housed

Order Codes

Buuze HF Gear
T5 2 x 28/54W WACO880.03.2.20.1


Options

POLYCARBONATE END CAPS WACO880.08.0.00.0
ANODISED ALUMINIUM END CAPS WACO880.09.0.20.0


Lamp Performance

Wattage	IL@25°C	Lamp Life
1 x 28W T5	2625	24,000hrs
1 x 54W T5	4450	24,000hrs

Dimensions



Photometric Performance



- 2 x 54W T5
- LOR = 46.1%
- SHR MAX = 1.61

Utilisation Factors UF(F)

Room Reflectance	Room Index
C W F	1.00 3.00 5.00
0.70 0.50 0.20	0.61 0.82 0.89

To Specify

Suspended linear luminaire with an anodised aluminium body and circular polycarbonate diffuser – as Whitecroft Lighting BUUZE

