



centurion

IP65 surface mounted amenity luminaire

Optics

- Lamp options:
 - 1 x 28/38W 2D T5
 - 1 x 18/26W TC-D

Body

- Die-cast aluminium housing and front bezel
- Two sizes of luminaire:
 - 350 is available with smooth, grill, or wave front
 - 265 is available with smooth, grill, or hood front
- Injection moulded opal polycarbonate diffuser UV stabilised to prevent yellowing
- Polyester powder coat finish in black or silver
- Two cable entry glands on rear 7.5mm – 13.5mm and BESA fixing on rear casting
- Silicon rubber gasket and captive stainless steel fixing screws
- IP65
- Integral switchstart control gear



centurion 265

> weblink > **CEN265**

ORDER CODES

Centurion 265 Smooth (Black)	Surface Mounted	3 hr Emergency
TC-D 1 x 18W	CENS18SB	CENS18SBEM
TC-D 1 x 26W	CENS26SB	CENS26SBEM
Centurion 265 Grill (Black)	Surface Mounted	3 hr Emergency
TC-D 1 x 18W	CENS18GB	CENS18GBEM
TC-D 1 x 26W	CENS26GB	CENS26GBEM
Centurion 265 Hood (Black)	Surface Mounted	3 hr Emergency
TC-D 1 x 18W	CENS18HB	CENS18HBEM
TC-D 1 x 26W	CENS26HB	CENS26HBEM

Options


EASYTEST	Add suffix /ET to order code	i.e. CENS18SB/ ET
SILVER	Replace B with S in order code	i.e. CENS18 SS



LAMP PERFORMANCE

Wattage	IL@25°C	Lamp Life
1 x 18W TC-D	1200	12,000hrs
1 x 26W TC-D	1800	12,000hrs

DIMENSIONS



Version	Ø	W	KG	KG
Smooth	265	90	5.0	6.0
Grill	265	100	5.0	6.0
Hood	265	100	5.0	6.0
Emergency	260	130	5.0	6.0




Smooth



Hood

PHOTOMETRIC PERFORMANCE



1 x 26W TC-D
Smooth
• LOR = 24%

TO SPECIFY

Circular surface cast aluminium bulkhead with 18/26W TC-D lamp. Smooth/grill/hood front design. Opal polycarbonate diffuser. IP65 – as Whitecroft Lighting CENTURION 265

