



Optics

- Light source options:
 - LED 700 lumens (3K – 19W*)
 - LED 900 lumens (3K – 28W*)
 - LED 800 lumens (4K – 19W*)
 - LED 1100 lumens (4K – 28W*)

Or

- 1 x 28/38W 2D T5
- 1 x 18/26W TC-D

**Total power consumption including driver*

Body

- Die-cast aluminium housing and front bezel
- Two sizes of luminaire:
 - 350 is available with smooth, grill, or wave front
 - 265 is available with smooth, grill, or hood front
- Injection moulded opal polycarbonate diffuser UV stabilised to prevent yellowing
- Polyester powder coat finish in black or silver
- Two cable entry glands and BESA fixing on rear casting
- Silicon rubber gasket and captive stainless steel fixing screws**
- IP65
- HF control gear
- Optional Command 5 microwave sensor mounted behind the diffuser (Centurion 350 LED only)

***LED product not suitable for cable entry via the BESA fixing*



centurion 350 LED

IP65 surface mounted
amenity luminaire



Order Codes

Centurion 350 LED Smooth (Black)	Fixed Output	3 hr Emergency
700 lumens 3K	CL703KDSB	CL703KDSBEM
900 lumens 3K	CL903KDSB	CL903KDSBEM
800 lumens 4K	CL804KDSB	CL804KDSBEM
1100 lumens 4K	CL1104KDSB	CL1104KDSBEM

Centurion 350 LED Grill (Black)	Fixed Output	3 hr Emergency
700 lumens 3K	CL703KDGB	CL703KDGBEM
900 lumens 3K	CL903KDGB	CL903KDGBEM
800 lumens 4K	CL804KDGB	CL804KDGBEM
1100 lumens 4K	CL1104KDGB	CL1104KDGBEM


Centurion 350 LED Wave (Black)	Fixed Output	3 hr Emergency
700 lumens 3K	CL703KDWB	CL703KDWBEM
900 lumens 3K	CL903KDWB	CL903KDWBEM
800 lumens 4K	CL804KDWB	CL804KDWBEM
1100 lumens 4K	CL1104KDWB	CL1104KDWBEM

Options

EASYTEST	Add suffix /ET	i.e. CL703KDSB/ET
COMEPS	Add suffix /EP	i.e. CL703KDSB/EP
SILVER	Replace B with S	i.e. CL703KDS
COMMAND 5	Replace L with Q5	i.e. CQ5703KDSB



Dimensions



Version	Ø	W	KG	KG
Smooth	350	125	3.4	3.7
Grill	350	125	3.4	3.7
Wave	350	125	3.4	3.7



Wave




Grill

LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
3K	≥ 80	L ₇₀ (50,000hrs)	MacAdam 4 SDCM
4K	≥ 80	L ₇₀ (50,000hrs)	MacAdam 4 SDCM

Photometric Performance



19W LED
Smooth Front
• LOR = 100%

To Specify

Circular surface mounted, cast aluminium IP65 bulkhead with 19W / 28W LED light source. Smooth/grill/wave front design with opal polycarbonate diffuser – as Whitecroft Lighting Centurion 350 LED

centurion 350

IP65 surface mounted
amenity luminaire



Order Codes

Centurion 350 Smooth (Black)	Surface Mounted	3 hr Emergency
2D T5 1 x 28W	CENS282DSB	CENS282DSBEM
2D T5 1 x 38W	CENS382DSB	CENS382DSBEM

Centurion 350 Grill (Black)	Surface Mounted	3 hr Emergency
2D T5 1 x 28W	CENS282DGB	CENS282DGBEM
2D T5 1 x 38W	CENS382DGB	CENS382DGBEM

Centurion 350 Wave (Black)	Surface Mounted	3 hr Emergency
2D T5 1 x 28W	CENS282DWB	CENS282DWBEM
2D T5 1 x 38W	CENS382DWB	CENS382DWBEM

Options


EASYTEST	Add suffix /ET	i.e. CENS282DSB/ET
SILVER	Replace B with S	i.e. CENS282DSS



Lamp Performance

Wattage	IL@25°C	Lamp Life
1 x 28W 2D T5	2150	21,000hrs
1 x 38W 2D T5	3020	21,000hrs

Dimensions



Version	Ø	W	KG	KG
Smooth	350	125	6.0	7.0
Grill	350	125	6.0	7.0
Wave	350	125	6.0	7.0




Smooth



Grill

Photometric Performance



1 x 28W 2D T5
Smooth
• LOR = 24%

To Specify

Circular surface mounted, cast aluminium bulkhead with 28/38W 2D T5 lamp. Smooth/grill/wave front design. Opal polycarbonate diffuser. IP65 – as Whitecroft Lighting Centurion 350

centurion 265

IP65 surface mounted
amenity luminaire



Order Codes

Centurion 265 Smooth (Black)	Surface Mounted	3 hr Emergency
TC-D 1 x 18W	CENS18SB	CENS18SBEM
TC-D 1 x 26W	CENS26SB	CENS26SBEM

Centurion 265 Grill (Black)	Surface Mounted	3 hr Emergency
TC-D 1 x 18W	CENS18GB	CENS18GBEM
TC-D 1 x 26W	CENS26GB	CENS26GBEM

Centurion 265 Hood (Black)	Surface Mounted	3 hr Emergency
TC-D 1 x 18W	CENS18HB	CENS18HBEM
TC-D 1 x 26W	CENS26HB	CENS26HBEM

Options


SILVER	Replace B with S	i.e. CENS18SS
--------	------------------	---------------



Lamp Performance

Wattage	IL@25°C	Lamp Life
1 x 18W TC-D	1200	13,000hrs
1 x 26W TC-D	1800	13,000hrs

Dimensions



Version	Ø	W	KG	KG
Smooth	265	90	5.0	6.0
Grill	265	100	5.0	6.0
Hood	265	100	5.0	6.0
Emergency	260	130	5.0	6.0




Smooth



Hood

Photometric Performance



1 x 26W TC-D
Smooth
• LOR = 24%

To Specify

Circular surface cast aluminium bulkhead with 18/26W TC-D lamp. Smooth/ grill/hood front design. Opal polycarbonate diffuser. IP65 – as Whitecroft Lighting CENTURION 265