

# centurion 350

IP65 surface mounted  
amenity luminaire



### Order Codes

|                              |                 |                |
|------------------------------|-----------------|----------------|
| Centurion 350 Smooth (Black) | Surface Mounted | 3 hr Emergency |
| 2D T5 1 x 28W                | CENS282DSB      | CENS282DSBEM   |
| 2D T5 1 x 38W                | CENS382DSB      | CENS382DSBEM   |

|                             |                 |                |
|-----------------------------|-----------------|----------------|
| Centurion 350 Grill (Black) | Surface Mounted | 3 hr Emergency |
| 2D T5 1 x 28W               | CENS282DGB      | CENS282DGBEM   |
| 2D T5 1 x 38W               | CENS382DGB      | CENS382DGBEM   |

|                            |                 |                |
|----------------------------|-----------------|----------------|
| Centurion 350 Wave (Black) | Surface Mounted | 3 hr Emergency |
| 2D T5 1 x 28W              | CENS282DWB      | CENS282DWBEM   |
| 2D T5 1 x 38W              | CENS382DWB      | CENS382DWBEM   |

### Options


|          |                  |                    |
|----------|------------------|--------------------|
| EASYTEST | Add suffix /ET   | i.e. CENS282DSB/ET |
| SILVER   | Replace B with S | i.e. CENS282DSS    |



### Lamp Performance

| Wattage       | IL@25°C | Lamp Life |
|---------------|---------|-----------|
| 1 x 28W 2D T5 | 2150    | 21,000hrs |
| 1 x 38W 2D T5 | 3020    | 21,000hrs |

### Dimensions



| Version | Ø   | W   | KG  | KG  |
|---------|-----|-----|-----|-----|
| Smooth  | 350 | 125 | 6.0 | 7.0 |
| Grill   | 350 | 125 | 6.0 | 7.0 |
| Wave    | 350 | 125 | 6.0 | 7.0 |




Smooth



Grill

### Photometric Performance



1 x 28W 2D T5  
Smooth  
• LOR = 24%

### To Specify

Circular surface mounted, cast aluminium bulkhead with 28/38W 2D T5 lamp. Smooth/grill/wave front design. Opal polycarbonate diffuser. IP65 – as Whitecroft Lighting Centurion 350