

centurion 350 LED

IP65 surface mounted
amenity luminaire



Order Codes

Centurion 350 LED Smooth (Black)	Fixed Output	3 hr Emergency
700 lumens 3K	CL703KDSB	CL703KDSBEM
900 lumens 3K	CL903KDSB	CL903KDSBEM
800 lumens 4K	CL804KDSB	CL804KDSBEM
1100 lumens 4K	CL1104KDSB	CL1104KDSBEM

Centurion 350 LED Grill (Black)	Fixed Output	3 hr Emergency
700 lumens 3K	CL703KDGB	CL703KDGBEM
900 lumens 3K	CL903KDGB	CL903KDGBEM
800 lumens 4K	CL804KDGB	CL804KDGBEM
1100 lumens 4K	CL1104KDGB	CL1104KDGBEM


Centurion 350 LED Wave (Black)	Fixed Output	3 hr Emergency
700 lumens 3K	CL703KDWB	CL703KDWBEM
900 lumens 3K	CL903KDWB	CL903KDWBEM
800 lumens 4K	CL804KDWB	CL804KDWBEM
1100 lumens 4K	CL1104KDWB	CL1104KDWBEM

Options

EASYTEST	Add suffix /ET	i.e. CL703KDSB/ET
COMEPS	Add suffix /EP	i.e. CL703KDSB/EP
SILVER	Replace B with S	i.e. CL703KDS
COMMAND 5	Replace L with Q5	i.e. CQ5703KDSB



Dimensions



Version	Ø	W	KG	KG
Smooth	350	125	3.4	3.7
Grill	350	125	3.4	3.7
Wave	350	125	3.4	3.7



Wave




Grill

LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
3K	≥ 80	L ₇₀ (50,000hrs)	MacAdam 4 SDCM
4K	≥ 80	L ₇₀ (50,000hrs)	MacAdam 4 SDCM

Photometric Performance



19W LED
Smooth Front
• LOR = 100%

To Specify

Circular surface mounted, cast aluminium IP65 bulkhead with 19W / 28W LED light source. Smooth/grill/wave front design with opal polycarbonate diffuser – as Whitecroft Lighting Centurion 350 LED