

centurion PG54

IP54 perimeter security lighting bulkhead

> weblink > **CENPG**

Optics

- Lamp options:
 - 70/150W HQI-E
 - 70/150W SON-E

Body


- IP54
- Black die cast aluminium body and diffuser frame
- Diffuser lens in heat resistant prismatic toughened glass
- Mounting can be direct to the wall or via a BESA box fixing (Do not mount on combustible surfaces)
- Integral photocell option
- Ambient operating temperature range -40°C to +25°C



ORDER CODES

Centurion PG54	Standard	Photocell
HQI-E 70W	CENG70H	CENG70HPC
HQI-E 150W	CENG150H	CENG150HPC
SON-E 70W	CENG70S	CENG70SPC
SON-E 150W	CENG150S	CENG150SPC


DIMENSIONS



LAMP PERFORMANCE

Wattage	IL@25°C	Lamp Life
70W HQI-E	6000	12,500hrs
150W HQI-E	13000	12,500hrs
70W SON-E	5600	28,500hrs
150W SON-E	14000	28,500hrs

PHOTOMETRIC PERFORMANCE



TO SPECIFY

IP54 perimeter lighting bulkhead to be suitable for direct surface or BESA box mounting. Body and frame to be in die cast aluminium finished black front. Heat resistant toughened glass prismatic diffuser lens, hinged for ease of lamp change with timed ignitor – as Whitecroft Lighting CENTURION PG54