

centurion PP65

IP65 perimeter security lighting bulkhead



Optics

- Lamp options:
 - 26W TC-D
 - 42W TC-T
 - 70W SON-E
 - 70W HQI-E

Body

- IP65
- Black polycarbonate base and visor
- Clear UV stabilised prismatic polycarbonate diffuser
- Two 20mm dia knock-out options for the cable entry gland either side of the base
- Integral photocell option
- Integral emergency option on 26W – TC-D only (may not achieve design output at low ambient temperatures)
- Ambient operating temperature ranges:
 - Non Emergency, -30°C to +25°C
 - Emergency, -5°C to + 25°C



Order Codes


Centurion PP65	Standard	Photocell
HQI-E 70W	CENP70H	CENP70HP
SON-E 70W	CENP70S	CENP70SP
TC-D 26W	CENP26	CENP26P
TC-D 26W Emergency	CENP26EMIN	CENP26PEMIN
TC-T 42W	CENP42	CENP42P

Options

UPLIGHT CONTROLLER* Add suffix **/UC** i.e. CENP70H/**UC**


* Only available with HQI-E 70W and TC-D 26W lamp options

Dimensions



L	H	W	KG	KG
260	290	192	2.0	3.0

Photometric Performance



- 1 x 70W SON-E
- LOR = 78%

Lamp Performance

Wattage	IL@25°C	Lamp Life
26W TC-D	1800	13,000hrs
42W TC-T	3200	13,000hrs
70W SON-E	5810	28,500hrs
70W HQI-E	7230	12,500hrs

To Specify

IP65 perimeter security lighting bulkhead suitable for direct surface mounting with a 4 point fixing employing two key slots and 2 locking screws and timed ignitor on SON versions. Black polycarbonate base and visor and UV stabilised prismatic polycarbonate diffuser. Fluorescent and HID lamp options – as Whitecroft Lighting CENTURION PP65