

# centurion PP65

IP65 perimeter security lighting bulkhead

> weblink > **CENPP**

### Optics

- Lamp options:
  - 26W TC-D
  - 42W TC-T
  - 70W SON-E
  - 70W HQL-E

### Body

- IP65
- Black polycarbonate base and visor
- Clear UV stabilised prismatic polycarbonate diffuser
- Two 20mm dia knock-out options for the cable entry gland either side of the base
- Integral photocell option
- Integral emergency option on 26W – TC-D only (may not achieve design output at low ambient temperatures)
- Ambient operating temperature range -30°C to +25°C




### ORDER CODES

| Centurion PP65     | Standard   | Photocell   |
|--------------------|------------|-------------|
| HQL-E 70W          | CENP70H    | CENP70HP    |
| SON-E 70W          | CENP70S    | CENP70SP    |
| TC-D 26W           | CENP26     | CENP26P     |
| TC-D 26W Emergency | CENP26EMIN | CENP26PEMIN |
| TC-T 42W           | CENP42     | CENP42P     |


### LAMP PERFORMANCE

| Wattage   | IL@25°C | Lamp Life |
|-----------|---------|-----------|
| 26W TC-D  | 1800    | 12,000hrs |
| 42W TC-T  | 3200    | 12,000hrs |
| 70W SON-E | 5600    | 28,500hrs |
| 70W HQL-E | 6000    | 12,500hrs |

### DIMENSIONS



### PHOTOMETRIC PERFORMANCE



### TO SPECIFY

IP65 perimeter security lighting bulkhead suitable for direct surface mounting with a 4 point fixing employing two key slots and 2 locking screws and timed ignitor on SON versions. Black polycarbonate base and visor and UV stabilised prismatic polycarbonate diffuser. Fluorescent and HID lamp options – as Whitecroft Lighting CENTURION PP65