

centurion PP65 LED

IP65 perimeter security
LED lighting bulkhead



Optics

- Light Output Options:
 - 3200 lumens, 50W

Body

- IP65
- DALI as standard
- 4000K
- Black polycarbonate visor and die-cast aluminium base
- Clear UV stabilised prismatic polycarbonate diffuser with Miro 5 reflector mounted internally
- Two 20mm diameter knock-out options for cable entry gland at either side of the base
- Ambient operating temperature ranges:
 - Non Emergency, -30°C to +25°C
 - Emergency, -5°C to + 25°C
- Integral emergency options in standard 3 hour, Easytest and COMECS



Order Codes

Centurion PP65 LED
3200 lumen, 50W

DALI
CENPL1Y

3hr Emergency
CENPL1YEM


Options

EASYTEST
COMECS

Add suffix /ET
Add suffix /EP

i.e. CENPL1Y/ET
i.e. CENPL1Y/EP

Dimensions



L	D	H	KG	KG
350	212	330	6.2	6.6

LED Performance

Colour Temp
4000K

Ra (CRI)
≥ 80

Life Expectancy
L₇₀ (50,000hrs)


Colour Consistency
MacAdam 4 SDCM

Equivalent Lamp Types

3200 lumens

SON-E 70W

Photometric Performance



50W 3200 lumen
4000K
• LOR = 100%
• SHR MAX = 1.28

To Specify

IP65 perimeter security LED lighting bulkhead suitable for direct surface mounting with a 4 point fixing employing two key slots and 2 locking screws. Black polycarbonate visor and die-cast aluminium base with UV stabilised prismatic polycarbonate diffuser and Miro 5 reflector – as Whitecroft Lighting CENTURION PP65 LED.