

centurion PP65 LED

IP65 perimeter security
LED lighting bulkhead



Optics

- Light Output Options:
 - 1250 lumens, 21W
 - 3200 lumens, 49W

Body

- IP65
- DALI as standard
- 4000K
- Black polycarbonate visor and die-cast aluminium base
- Clear UV stabilised prismatic polycarbonate diffuser with Miro 5 reflector mounted internally
- Two 20mm diameter knock-out options for cable entry gland at either side of the base
- Ambient operating temperature ranges:
 - Non Emergency, -30°C to +25°C
 - Emergency, -5°C to + 25°C
- Integral emergency options in standard 3hr, Easytest and COMECS




Order Codes

Centurion PP65 LED	DALI	3hr Emergency
1250 lumen, 21W	CENPL0Y	CENPL0YEM
3200 lumen, 49W	CENPL1Y	CENPL1YEM

Options

EASYTEST	Add suffix /ET	i.e. CENPL1Y/ET
COMECS	Add suffix /EP	i.e. CENPL1Y/EP

Dimensions



L	D	H	KG	KG
350	212	330	6.2	6.6


LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	≥ 80	L ₇₀ (50,000hrs)	MacAdam 4 SDCM

Equivalent Lamp Types

1250 lumens	TC-D 26W
3200 lumens	SON-E 70W

Photometric Performance



49W 3200 lumen
4000K
• LOR = 100%
• SHR MAX = 1.28

To Specify

IP65 perimeter security LED lighting bulkhead suitable for direct surface mounting with a 4 point fixing employing two key slots and 2 locking screws. Black polycarbonate visor and die-cast aluminium base with UV stabilised prismatic polycarbonate diffuser and Miro 5 reflector – as Whitecroft Lighting CENTURION PP65 LED.

Exterior