



Optics

- Two different sized heads:
 - Circo Fast 125 for 20/35W CDM-Tm
 - Circo Fast 190 for 35/70/150W CDM-T or 100W White SON
- CDM available with medium or wide distribution
- SON wide distribution only
- Specular anodised aluminium reflector with integral safety glass

Body

- Bezel painted white
- Easy installation using spring clips
- Supplied with ST18/3 plug for electronic gearbox connection.
(Order gearbox separately)
- Suitable for ceiling thickness of 3-20mm



Order Codes

Circo Fast 125
CDM-Tm 20/35W

Wide Reflector
FAS-C20-35-W

Medium Reflector
FAS-C20-35-M

Circo Fast 190
CDM-T 35/70/150W
SON WHITE 100W


Wide Reflector
FAS-C35-150-W
FAS-S100-W

Medium Reflector
FAS-C35-150-M
-

Gearbox
CDM-Tm 20W
CDM-Tm 35W
CDM 35W
CDM 70W
CDM 150W
SON WHITE 100W

HF
GB-C20TME-P
GB-C35TME-P
GB-C35E-P
GB-C70E-P
GB-C15E-P
GB-S100E-P

Dimensions



Version	H	Ø	CAØ	KG
Circo Fast 125	133	125	118	1.8
Circo Fast 190	203	190	175	2.4

Photometric Performance

70W CDM-T				70W CDM-T				20W CDM-Tm				20W CDM-Tm					
M	LUX	70W	Ø	M	LUX	70W	Ø	M	LUX	20W	Ø	M	LUX	20W	Ø		
1.0m	13296	0.7	1.0m	5198	1.4	1.0m	6187	0.5	1.0m	1279	1.3	1.0m	320	2.7	1.0m	80	5.4
2.0m	3324	1.4	2.0m	1300	2.8	2.0m	1547	0.9	2.0m	320	2.7	2.0m	80	5.4	2.0m	80	5.4
3.0m	1477	2.2	3.0m	578	4.3	3.0m	687	1.4	3.0m	142	4.0	3.0m	142	4.0	3.0m	80	5.4
4.0m	831	2.9	4.0m	325	5.7	4.0m	387	1.9	4.0m	80	5.4	4.0m	80	5.4	4.0m	80	5.4
Medium 40°				Wide 71°				Medium 26°				Wide 68°					

To Specify

Circo Fast 125
Fixed downlighter for 20W or 35W CDM-Tm. Die cast aluminium body with white 126mm Ø bezel and specular aluminium reflector giving medium (40°) or wide (71°) distribution – as Whitecroft Lighting CIRCO FAST 125

Circo Fast 190
Fixed downlighter for 35/70/150W CDM-T or 100W STH lamp. Die cast aluminium body with white 188mm Ø bezel and specular aluminium reflector giving medium (40°) or wide (71°) CDM/62° SON distribution – as Whitecroft Lighting CIRCO FAST 190