

cirrus

direct/indirect recessed luminaire

> weblink > **CIR3**

Optics

- Lamp options:
 - 1 or 2 x 28/54W T5
- Semi-specular retained louvre with perforated wings

Body

- Steel body finished white
- Designed to rest on a 300 x 1200mm exposed T 15mm ceiling and align with tegular tiles
- Designed to rest above exposed T 25mm ceilings



ORDER CODES

Cirrus	HF Gear	3 hr Emergency
T5 1 x 28W	CRSH128	CRSH128EMIN
T5 2 x 28W	CRSH228	CRSH228EMIN
T5 1 x 54W	CRSH154	CRSH154EMIN
T5 2 x 54W	CRSH254	CRSH254EMIN

Options


DALI DIMMING	Replace H with Y in order code	i.e. CRS Y 128
DSI DIMMING	Replace H with D in order code	i.e. CRS D 128
SWITCH DIMMING	Replace H with X in order code	i.e. CRS X 128
COMMAND 4	Replace H with Q4Y in order code	i.e. CRS Q4Y 128
EASYTEST	Add suffix /ET to order code	i.e. CRSH128/ ET
COMET	Add suffix /CT to order code	i.e. CRSH128/ CT

LAMP PERFORMANCE

Wattage	IL@25°C	Lamp Life
1 x 28W T5	2600	24,000hrs
1 x 54W T5	4450	24,000hrs

PERFORMANCE GUIDE

Lamps	Illuminance	Spacing
2 x 28W T5	480 lux	2.4m x 2.4m



Maintenance: 0.8
 Reflectance: 70/50/20
 Ceiling Height: 2.7m
 Working Plane: 0.8m


CEILING INTEGRATION

Refer to common ceiling compatibility matrix – See page 310

Exposed T Grids


T25 Lay in
 T15 Tegular

DIMENSIONS



L	W	H	KG	KG
1184	284	133	5.0	6.0

PHOTOMETRIC PERFORMANCE



2 x 28W T5
 • LOR = 61.8%
 • SHR MAX = 1.53

Utilisation Factors UF(F)

Room Reflectance			Room Index		
C	W	F	1.00	3.00	5.00
0.70	0.50	0.20	0.50	0.64	0.67

TO SPECIFY

Fully recessed T5 direct/indirect architectural luminaire with perforated opal lined gull winged semi-specular louvre giving diffuse illumination – as Whitecroft Lighting CIRRUS