

integrated intelligent detector/photocells

> weblink > **COM3**
> **COM4**

- Integrated detector
- Programmable via the COMAP and COMPTC programmer
- Regulating photocell ensures minimum maintained light level taking into account the contribution from adjacent luminaires and daylight
- Detects movement up to 6m diameter
- 5-35 minute time delay including 10 second walk test
- Remote switching via hand held controller
- Wall switch override to adjust light level or turn luminaires on or off (COM4 DALI only)
- DALI versions can control master and slave - contact our technical department for further information



Command 3



Command 4

ORDER CODES

COM3 DALI PIR Detector

See luminaire pages for order codes

COM4 Analogue PIR Detector

See luminaire pages for order codes

COM4 DALI PIR Detector

See luminaire pages for order codes




COM3 Infill mounted option



COM4 louver mounted option

Look for the  or  symbol

DETECTION RANGE



ACCESSORIES (see page 183)



Advance programmer COMAP



Hand held programmer COMPTC



Hand held controller COMHHC and COMSSC

Detector	Mounting type	Detector type	Detector range	Max ceiling height	Control method	Detection method	Occupancy type	Off delay	Daylight hold off	Daylight regulating	Programmable	Maximum load
Integrated PIR Detector COM3	Integrated	360	Ø 6m @ 2.4m	3m	DALI	PIR	Presence Absence	5-35 min	Yes	Yes	Yes	2 DALI
Integrated PIR Detector COM4	Integrated	360	Ø 6m @ 2.4m	3m	Analogue 1-10V/ DALI	PIR	Presence Absence	5-35 min	Yes	Yes	Yes	6 amp / 2 DALI /