

concert EX1S

surface or suspended
LED exit luminaire



Optics

- Power consumption
– 12W maintained
- 28m viewing distance
- 15 long life white LEDs
- Complete with double sided acrylic legend panel in up, down, left/right as standard
- Legends supplied in accordance with BS 5266-1 2011 (ISO7010)

Body

- Wall, flag, ceiling or suspended mounting
- Mounting accessories required for installation to be ordered separately
- Extruded aluminium housing with brushed finish
- Smaller than conventional recessed exit signs making installation look more attractive
- 3 hour maintained (may be wired as non-maintained)
- Complete with Ni-Cd cells

Order Codes

Concert EX1S

12W, with UP legend supplied
12W, with DOWN legend supplied
12W, with LEFT/RIGHT legend supplied

3 hr Emergency

EX1SMU/7010
EX1SMD/7010
EX1SMLR/7010

Options

CEILING MOUNTING BRACKET	EX1SCBRK
WALL MOUNTING BRACKET	EX1SWBRK
END FIXING (FLAG) MOUNTING BRACKET	EX1SEBRK
WIRE SUSPENSION KIT	Adjustable to 1 metre maximum EX1SWIRE
COMEPS	Add suffix /EP i.e. EX1SMU/7010/EP*

Note: Mounting brackets to be ordered separately

*Can be wired as Easytest if required

Legends



Up

Down




Left

Right



Ceiling Bracket



End Fixing Bracket




Wall Bracket



Wire Suspension Kit

Dimensions



L	W	H	H ₁	KG
300	50	220	150	1.2

To Specify

Surface or suspended LED exit luminaire with 15 long life LEDs – as Whitecroft Lighting CONCERT EX1S