

concert EX2S

wall mounted LED low
profile exit luminaire



Optics

- Power consumption
 - 10W maintained
 - 7W non-maintained
- 25 metre viewing distance
- 15 long life LEDs within a matrix dot coated reflector system for even illumination
- Complete with acrylic legend panel with down arrow as standard
- Legends supplied in accordance with BS 5266-1 2011 (ISO7010)

Body

- Wall mounted 'picture frame' style slim style steel body
- Wall mounted via key hole slot fixings
- Two part body for ease of installation, cover hooks over the backplate and is simply retained below
- High temperature Ni-Cd battery with constant current charger and LED charge indicator
- 3 hour maintained (may be wired as non-maintained)
- BESA cable entry




Order Codes

Concert EX2S	Legend	3 hr Emergency
LED Emergency Bulkhead	DOWN	3 hour maintained EX2S/7010
LED Emergency Bulkhead	LEFT	3 hour maintained EX2AL/7010
LED Emergency Bulkhead	RIGHT	3 hour maintained EX2AR/7010
LED Emergency Bulkhead	UP	3 hour maintained EX2AU/7010

Options

EASYTEST	Add suffix /ET	i.e. EX2S/7010/ET
COMEPS	Add suffix /EP	i.e. EX2S/7010/EP

Dimensions



L	W	H	KG
315	30	190	1.4

Legends



Up



Down



Left



Right

To Specify

Surface mounted slim LED 'picture frame' style emergency exit sign
– as Whitecroft Lighting EX2S