



Recessed



Wire Suspended

Optics

- Power consumption;
 - 8W maintained
 - 4.6W non-maintained
- 20m viewing distance
- 10 long life, high output LEDs within a matrix dot coated reflector system for even illumination
- Each LED chip is alternately powered so if one fails, the legend remains lit
- Luminaire supplied with polycarbonate UP legend as standard
- Down, left and right legends also available (supplied separately)
- Legends supplied in accordance with BS 5266-1 2011 (ISO7010)

Body

- Maintained as standard but may be wired as non maintained
- IP20
- Available in wall, recessed and wire suspended mounting options
- Slim architectural design with framed exit sign legend
- Legends can be changed without tools
- 6.4V Li-Fe battery with constant current charger and LED charge indicator
- Ambient 0 – 25°C
- COMECS addressable emergency as standard (can be wired as Easytest)
- Can be connected to a wider DALI Command Elite system across a room or building if required

concert EX3S

Order Codes

Concert EX3S
Wall mounted with UP legend
Recessed mounted with UP legend
Wire suspended with UP legend

Wall Legends

DOWN
LEFT
RIGHT

Suspended and Recessed Legends

DOWN
LEFT
RIGHT

*Can be wired as Easytest if required

Legends



Up Down



Left Right


COMEPS*
EX3SWM/EP
EX3SRM/EP
EX3SSM/EP

One sided
EX3S7010D
EX3S7010L
EX3S7010R

Double sided
EX3S7010DD
EX3S7010DL
EX3S7010DR


Dimensions

Wall mounted




L	L ₁	W	H	H ₁	KG
237	208	46	137	109	1.3

Recessed



L	L ₁	W	H	H ₁	KG
237	275	65	140	85	1.2

Wire suspended



L	L ₁	W	H	H ₁	KG
237	275	65	140	-	1.2

To Specify

LED IP20, DALI addressable self-contained maintained or non-maintained emergency luminaire with rigid polycarbonate body and polycarbonate legends. Wall, ceiling, recessed or suspended mounting. Li-Fe battery with constant current charger and LED charge indicator - as Whitecroft Lighting CONCERT EX3S