

concert GL050

IP68 LED diffused low power
recessed luminaire



Optics

- Lamp options:
 - 3 x 1W LED. Available in cool white, blue and RGB colour change.
 - All require separate driver
- Walk over, toughened frosted glass cover

Body

- IP68. 'Anti-Siphon' system prevents ingress via cable entry
- Marine grade stainless steel (316) body
- Suitable for in ground, wall or ceiling mounting
- For in ground application, use 1st fix installation tube
- IP66 junction box available for connection between luminaire and driver



Order Codes

Concert GL050

3 x 1W White

CNGL050WC

3 x 1W Blue

CNGL050BL

3 x 1W RGB Colour Change

CNGL050RGB

Installation Tube

(In ground application)

CNTUBE/68

Driver for White/Blue* Drives up to 3 blue/white luminaires

CNPLU/3501-9

Dimmable Driver for white/blue

Drives up to 4 blue/white luminaires

CNPLD/1-16

Driver for RGB*

Drives up to 4 RGB luminaires

CNRGBOX

Junction box 4 way IP66

For white/blue only

CNJB2



IP66 Junction box

For RGB only

CNJB3

*See page 74 for details of RGB controls

Dimensions



Photometric Performance

Due to the continual development in LED technology, please contact our Technical Desk for up to date photometric data

To Specify

IP68 in ground 3W LED luminaire, with marine grade (316) stainless steel body and frosted glass front cover – as Whitecroft Lighting CONCERT GL050