

Starline

- Up to IP65 when used in conjunction with additional waterproof connector
- Aluminium slimline channel complete with fixing brackets
- Complete with 150mm connecting cables, with standard connectors, at each end for ease of installation
- Non IP65 plug & play connectors for simple connection pre-wired
- Beam angle - 110°
- High brightness LEDs in linear array mounted in aluminium alloy channel and covered by silicone resin

Driver

- 24V DC electronically stabilised constant voltage driver

Note: Drivers are not IP rated and should not be used in non weatherproof locations



Order Codes

Concert Starline

Starline 600 Warm White	10 Watt	CNSL3K600
Starline 600 Cool White	10 Watt	CNSL4K600
Starline 1200 Warm White	20 Watt	CNSL3K1200
Starline 1200 Cool White	20 Watt	CNSL4K1200


Driver

20 Watt	Runs upto 2 x 10W or 1 x 20W	CNSLD20
75 Watt	Runs upto 7 x 10W or 3 x 20W	CNSLD75

Accessories

QUICK WATERPROOF CONNECTOR (FOR LINKING STRIPS)	CNUY2
---	-------

Dimensions



Version	L	W	H	KG
Starline 600	620	20	6.2	0.1
Starline 1200	1220	20	6.2	0.2

To Specify

Linear LED strip luminaire with extruded aluminium body. Complete with pre-wired cables and connectors. IP65 when used with quick fix waterproof connectors – as Whitecroft Lighting CONCERT STARLINE