

concert WL050

LED low level wall finding luminaire

> weblink > **CO50**

ORDER CODES

Concert WL050


White	c/w 300mm lead	CNWL050WC
Blue	c/w 300mm lead	CNWL050BL
Wall box	For mounting in concrete	CNWL050WALLBOX
Driver	Drives up to 7 luminaires	CNPLU/3501-9
Dimmable Driver	Drives up to 12 luminaires	CNPLD/1-16

PHOTOMETRIC PERFORMANCE

Due to the continual development in LED technology, please contact our technical department for up to date photometric data



DIMENSIONS



D	W	H	KG
37	90	90	0.2



TO SPECIFY

Recessed 1.2W LED wall luminaire with shallow die cast aluminium body – as Whitecroft Lighting CONCERT WL050

concert line

LED linear wall wash strip

> weblink > **CLIN**

ORDER CODES

Concert Line

18W Cool White	c/w 3m lead	CNLEDLINEWC
12W RGB	c/w 3m lead	CNLEDLINERGB
Driver (for White)	Drives 1 x CNLEDLINEWC	CNPLU/7003-9
Dimmable Driver (for White)	Drives 1 x CNLEDLINEWC	CNPLD/1-16
Driver (for RGB)	Drives 1 x CNLEDLINERGB	CNRGBOX


See page 47 for RGB control specification

PHOTOMETRIC PERFORMANCE

Due to the continual development in LED technology, please contact our technical department for up to date photometric data



DIMENSIONS



L	W	H	KG
400	34	31	1.6



TO SPECIFY

IP65 rated linear LED strip luminaire with extruded body finished black and side cable entry allowing seamless continuous mounting – as Whitecroft Lighting CONCERT LINE