

cornice - d1 & d1E

Surface fluorescent: Asymmetric surface luminaire

APPLICATION

- Cornice lighting
- Concealed lighting
- Corridors
- Lighting over entrance thresholds

SPECIFICATION

- Lamp options:
Single 36W and 58W T8
- Fabricated steel construction
- White polyester powder paint finish
- High frequency control gear as standard
- IP20
- Supplied less lamps

Diffuser


- Prismatic acrylic diffuser
- Asymmetric light distribution
- Positive retention diffuser
- Minimal dirt and bug entry





DIMENSIONS AND WEIGHT

LAMP WAYS	WEIGHT KG
1 x 36W	5.1
1 x 58W	6.0



58W luminaire



36W luminaire



LAMP PERFORMANCE MATRIX

WATTAGE	IL@25°C	LAMP LIFE
1 x 36W T8	3350	15,000
1 x 58W T8	5200	15,000

ORDER CODES – CORNICE

ASYMMETRIC SURFACE LUMINAIRE

SUPPLIED LESS LAMPS

1 x 36W T8

1 x 58W T8


HIGH FREQUENCY

ODPH136

ODPH158

PHOTOMETRY

Cornice
ACRYLIC DIFFUSER
1 x 36W T8 Lamp



- LOR = 71.1%
- SHR MAX = 1.60

UTILISATION FACTORS UF(F)

Room Reflectance Room Index

SHR NOM=1.50

C	W	F	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.39	0.44	0.49	0.52	0.57	0.60	0.62	0.65	0.67
0.50	0.30	0.20	0.32	0.37	0.41	0.44	0.48	0.52	0.54	0.57	0.60
0.00	0.00	0.00	0.25	0.29	0.32	0.35	0.38	0.41	0.43	0.46	0.47

QuickLink

ODP

Go