

command plus CPDMHW4/8

programmable intelligent
hard wired hubs


- Programmable intelligent hard wired lighting control modules in either 4 or 8 channel outputs
- Connects multiple luminaires, presence detectors and SELV inputs
- Maximum 18W power consumption
- Operational Supply 230VAC ~50Hz/60Hz

Order Codes

Command Plus 4 port hard wired hub	CPDMHW4
Command Plus 4 port hard wired hub with DALI dimming card	CPDMHW4Y
Command Plus 4 port hard wired hub with communicating card and DALI dimming card	CPDMHW4BY
Command Plus 4 port hard wired hub with communicating card	CPDMHW4B
Command Plus 8 port hard wired hub	CPDMHW8
Command Plus 8 port hard wired hub with DALI dimming card	CPDMHW8Y
Command Plus 8 port hard wired hub with communicating card and DALI dimming card	CPDMHW8BY
Command Plus 8 port hard wired hub with communicating card	CPDMHW8B



Dimensions



Version	L	W	H	KG
CPDMHW4	213	91	62	0.55
CPDMHW8	213	91	62	0.62

command plus COMPLINT


control and
communication interface

- Control and communication interface
- BACnet interface with supervisory and scheduling control
- Command Plus bus to RS485 interface
- Programmable timed event scheduling
- Sharing of occupancy information with the BMS

Order Codes

COMPLINT	
Command Plus control and communication interface	COMPLINT

Dimensions



L	D	H	KG
197	58	321	1.36

