

cygnus sx

LED post top lantern for outdoor applications



Optics

- Light output options:
 - 2900 lumens (4000K - 55W)
- Symmetrical distribution
- Zero light pollution
- UV stabilised polycarbonate clear diffuser
- 70% light output after 60,000 hours life

Body

- Die cast aluminium
- Coated for corrosion and saline environment resistance
- IP66 IK08 rated protection
- 60mm diameter post top spigot
- Finished in Graphite Grey or Silver
- Supplied with IP67 rated 3 pole plug and socket
- Suitable for ambient temperatures between -20°C to +40°C



Order Codes

Cygnus SX

2900 lumen (55W)

Graphite Grey

CYX14KG


Options

SILVER

Replace G with S

i.e. CYX14KS

Dimensions



Ø
375

H
765

KG
7.7

WINDAGE M²: 0.165

LED Performance


Colour Temp
4000K

Ra (CRI)
≥ 80

Life Expectancy
L₇₀ (60,000hrs)

Colour Consistency
MacAdam 4 SDCM

Photometric Performance



55W 2900 lumen
• LOR = 100%

To Specify

IP66 LED post top lantern with tapered die cast aluminium body. With symmetrical distribution having zero upward light – as Whitecroft Lighting CYGNUS SX.