

- Manufactured from extruded aluminium with a maximum rating of 16A from a 240v mains supply
- The system comprises three individually controlled circuits for maximum flexibility and control. The design allows quick and easy connection and mounting
- Available in 2m and 3m lengths finished white or black
- Live and dead ends
- Straight and flexible connectors
- Surface or suspended ceiling fixings

Order Codes

Direct 3

2m length 3 circuit surface track

3m length 3 circuit surface track

Live end feed right

Live end feed left

Dead end

Straight connector

Flexible connector

Ceiling clamp (recommended every 600mm)

Wire suspension set (1500mm maximum length)

Point clamp suspension (must be ordered for use with wire suspension set)

Bending Tool

White

SHXTS4200W

SHXTS4300W

SHXTS11W

SHXTS12W

SHXTS41W

SHXTS21W

SHXTS23W

SHSKB12W

SHSPW1W

SHSP4PW

SHXTSV12

Options


BLACK

Replace W with B


i.e. SHXTS4200B

Note: Other accessories, track lengths and colours also available – please contact our sales office

Track Components




Straight Connector




Flex Corner Connector




Ceiling Clamp




Live End



Dead End




Point Clamp



Wire Suspension

Dimensions



To Specify

Three circuit extruded aluminium track with a maximum rating of 16A from a 240v mains supply compatible with Strato range spotlights. Three individually controlled circuits for maximum flexibility and control. Available in 2m and 3m lengths finished white with live and dead end fixings and for surface or suspended mounting – as Whitecroft Lighting DIRECT 3