

direct 3

Display: Mains voltage – 3 circuit track



APPLICATION


The Direct 3 surface mounted 3 circuit track system lends itself to applications where ease of installation is sought and it is of particular value if electric outlet points are not clearly defined in advance. Such needs are particularly likely to occur in:-

- Retail – accent and display lighting
- Wall-washing applications
- Museums and galleries
- Receptions
- Feature lighting

SPECIFICATION

- Direct 3 mounts Torque range spotlights when these are specified with track adapters
- Manufactured from extruded aluminium with a maximum rating of 16A from a 240v mains supply
- The system comprises three individually controlled circuits for maximum flexibility and control. The design allows quick and easy connection and mounting
- Available in 2m and 3m lengths finished White RAL 9010
- Live and dead end fixings
- Straight and flexible inter-connecting fixings
- Ceiling mounting clamp should be ordered for ceiling mounting – recommended spacing 600mm
- Wire suspension set should be ordered for suspended mounting – standard suspension height 1500mm. A point clamp suspension must be ordered separately for use with the wire suspension set

DIMENSIONS



TRACK COMPONENTS



Straight connector



Flex corner connector



Live end



Dead end



Ceiling clamp



Point clamp



Wire suspension



ORDER CODES – DIRECT 3 TRACK AND COMPONENTS

MAINS VOLTAGE 3 CIRCUIT TRACK

DESCRIPTION	CODE
2m length 3 circuit surface track RAL 9010	SHXTS4200W
3m length 3 circuit surface track RAL 9010	SHXTS4300W
Live end feed right	SHXTS11W
Live end feed left	SHXTS12W
Dead end	SHXTS41W
Straight connector	SHXTS21W
Flexible connector	SHXTS23W
Ceiling clamp	SHSKB12W
Wire suspension set (1500mm maximum length)	SHSPW1W
Point clamp suspension	SHSP4PW
Bending Tool	SHXTSV12

Note: Other accessories and track lengths also available – please contact our sales office

To specify state:

Three circuit extruded aluminium track with a maximum rating of 16A from a 240v mains supply compatible with Torque range spotlights. Three individually controlled circuits for maximum flexibility and control. To be available in 2m and 3m lengths finished White RAL 9010 with live and dead end fixings and for surface or suspended mounting – as Whitecroft Lighting DIRECT 3

QuickLink

3CIRC

Go