



DTFA elite – for modular ceilings

IP65/54 recessed luminaire with sealed twin frame construction

Optics

- Lamp options:
 - 4 x 14/24W T5
 - 2 or 4 x 28W T5
 - 2, 3 or 4 x 54W T5
- All optics are TP(a) rated:
 - Louvre above 4mm toughened glass or clear fireguard material
 - Prismatic acrylic above 4mm toughened glass
 - Single sheet 3mm prismatic fireguard material

Note – a glass front face resists all cleaning chemicals and is best for a sterile environment. Other TP(a) materials are selected for best chemical resistance if advice is needed contact the Whitecroft technical desk.

Body

- Front access only
- Welded steel body finished white
- Compatible with modular exposed T and spring T ceilings. Recessing panels are recommended on spring T ceilings to retain room integrity – Refer to page 310 for ceiling compatibility info
- Dual IP rated – to a BSI tested and certified construction as protecting the room to IP65 from void contamination with the front frame in place and IP54 with the frame removed
- Extruded aluminium outer frame (gasketed to the T bar) and inner frame integrated in line but at an angle to eliminate a vertical gap. Concealed front frame fixings and white full gloss frames
- The diffuser clamping system is highly secure and will accept glass. The inner frame design facilitates diffuser replacement
- Robust extruded aluminium side arm cam brackets adjusted from outside the sealed body



DTFA elite – for modular ceilings

> weblink > **DTFA**

ORDER CODES

Louvre above 4mm toughened glass	HF Gear	3 hr Emergency
T5 4 x 14W	DTFAWGH414	DTFAWGH414EMIN
T5 4 x 24W	DTFAWGH424	DTFAWGH424EMIN
T5 2 x 28W	DTFAWGH228	DTFAWGH228EMIN
T5 4 x 28W	DTFAWGH428	DTFAWGH428EMIN
T5 2 x 54W	DTFAWGH254	DTFAWGH254EMIN
T5 4 x 54W	DTFAWGH454	DTFAWGH454EMIN

Louvre above 3mm clear TP(a) rated sheet	HF Gear	3 hr Emergency
T5 4 x 14W	DTFAWFH414	DTFAWFH414EMIN
T5 4 x 24W	DTFAWFH424	DTFAWFH424EMIN
T5 2 x 28W	DTFAWFH228	DTFAWFH228EMIN
T5 4 x 28W	DTFAWFH428	DTFAWFH428EMIN
T5 2 x 54W	DTFAWFH254	DTFAWFH254EMIN
T5 4 x 54W	DTFAWFH454	DTFAWFH454EMIN

Prismatic acrylic above 4mm toughened glass	HF Gear	3 hr Emergency
T5 4 x 14W	DTFAAGH414	DTFAAGH414EMIN
T5 4 x 24W	DTFAAGH424	DTFAAGH424EMIN
T5 2 x 28W	DTFAAGH228	DTFAAGH228EMIN
T5 4 x 28W	DTFAAGH428	DTFAAGH428EMIN
T5 2 x 54W	DTFAAGH254	DTFAAGH254EMIN
T5 3 x 54W	DTFAAGH354	DTFAAGH354EMIN
T5 4 x 54W	DTFAAGH454	DTFAAGH454EMIN

Prismatic TP(a) single sheet	HF Gear	3 hr Emergency
T5 4 x 14W	DTFAKH414	DTFAKH414EMIN
T5 4 x 24W	DTFAKH424	DTFAKH424EMIN
T5 2 x 28W	DTFAKH228	DTFAKH228EMIN
T5 4 x 28W	DTFAKH428	DTFAKH428EMIN
T5 2 x 54W	DTFAKH254	DTFAKH254EMIN
T5 3 x 54W	DTFAKH354	DTFAKH354EMIN
T5 4 x 54W	DTFAKH454	DTFAKH454EMIN

Options

DALI DIMMING	Replace H with Y in order code	i.e. DTFAWGY414
DSI DIMMING	Replace H with D in order code	i.e. DTFAWGD414
SWITCH DIMMING	Replace H with X in order code	i.e. DTFAWGX414
EASYTEST	Add suffix /ET to order code	i.e. DTFAWGH414/ ET
COMET	Add suffix /CT to order code	i.e. DTFAWGH414/ CT

RECESSING PANEL to retain room integrity on spring T ceilings
14/24W lamps

RP600x600

28/54W twin lamp options

RP300x1200

28/54W three and four lamp options

RP600x1200




LAMP PERFORMANCE

Wattage	IL@25°C	Lamp Life
1 x 14W T5	1200	24,000hrs
1 x 24W T5	1750	24,000hrs
1 x 28W T5	2600	24,000hrs
1 x 54W T5	4450	24,000hrs

PERFORMANCE GUIDE


Lamps	Illuminance	Spacing
4 x 14W T5	465 lux	2.4m x 2.4m




Maintenance:
0.8
Reflectance:
70/50/20
Ceiling Height:
2.7m
Working Plane:
0.8m

DTFA elite – for modular ceilings


> weblink > **DTFA**



Cam jacking bracket



DIMENSIONS




WEIGHT

	Louvre/ toughened glass	Louvre/TP(a) rated sheet	Acrylic/ toughened glass	Prismatic TP(a)
T5 4 x 14W	15.0 KG	13.0 KG	16.0 KG	11.0 KG
T5 4 x 24W	15.0 KG	13.0 KG	16.0 KG	11.0 KG
T5 2 x 28W	16.0 KG	14.0 KG	17.0 KG	12.0 KG
T5 4 x 28W	26.0 KG	20.0 KG	27.0 KG	18.0 KG
T5 2 x 54W	16.0 KG	14.0 KG	17.0 KG	12.0 KG
T5 3 x 54W	–	–	27.0 KG	18.0 KG
T5 4 x 54W	26.0 KG	20.0 KG	27.0 KG	18.0 KG

Note: Emergency luminaire are 1 KG heavier than the standard shown above

PHOTOMETRIC PERFORMANCE



CEILING INTEGRATION

Refer to common ceiling compatibility matrix – See page 310

Exposed T Grids

T15/T25 Pull up

Spring T Grids

- SAS – 150/120
- Armstrong – Orcal 1800/3000
- Burgess – Clip in/Abar
- Dampa – Clip in

TO SPECIFY

Recessed modular T5 clean room luminaire to a BSI tested and certified construction as IP65 frame on IP54 frame off with twin in line extruded aluminium frames with angled integration and concealed front frame fixings, suspension via robust aluminium cam brackets adjusted from outside the luminaire – as Whitecroft Lighting DTFA ELITE T5

