

duo[®] 500 x 500 centre optic

> weblink > **DUO5**

ORDER CODES

Duo Living Louvre	HF Gear	3 hr Emergency
T5 4 x 14W	DUO5CH414VXT	DUO5CH414VXTMIN

Options

DALI DIMMING	Replace H with Y in order code	i.e. DUO5C Y 414VXT
DSI DIMMING	Replace H with D in order code	i.e. DUO5C D 414VXT
SWITCH DIMMING	Replace H with X in order code	i.e. DUO5C X 414VXT
EASYTEST	Add suffix /ET to order code	i.e. DUO5CH414VXT/ ET
COMET	Add suffix /CT to order code	i.e. DUO5CH414VXT/ CT




LAMP PERFORMANCE


Wattage	IL@25°C	Lamp Life
1 x 14W T5	1200	24,000hrs

PERFORMANCE GUIDE

Lamps	Illuminance	Spacing
4 x 14W T5	480 lux	2.5m x 2.0m



DIMENSIONS



L	W	H	L ₁	W ₁	KG	KG
493	493	101	571	475	4.2	5.5

CEILING INTEGRATION


Refer to common ceiling compatibility matrix – See page 310

Exposed T Grids

T25 Lay in

T15 Lay in

PHOTOMETRIC PERFORMANCE



4 x 14W T5
Living Louvre
• LOR = 54.6%
• SHR MAX = 1.67

Utilisation Factors UF(F)

Room Reflectance			Room Index		
C	W	F	1.00	3.00	5.00
0.70	0.50	0.20	0.41	0.54	0.58

TO SPECIFY

Recessed T5 500 x 500mm luminaire with dual optic configuration and air return facility. Incorporating Intermediate Brightness Zone element to diffuse light and graduate brightness across the ceiling, manufactured in a Tp(a) rated polycarbonate, and 1 optical cell with Living Louvre to control light and reduce glare – as Whitecroft Lighting DUO