


Optics

- Lamp options:
 - 3 x 24W T5
- Micro prism side controllers or living louvres covered by clear polycarbonate
- Satine Blend central diffuser for lamp diffusion
- Framed polycarbonate Tp(a) rated sheet for ease of cleaning
- Picture options for central diffuser to add feature

Body

- Sheet steel body and frame with a choice of comfort and brightness controlled optics. Combines Duo office lighting excellence with infection control and clean area expertise
- IP40 rated



Micro prism diffuser with opal central diffuser



Living louvre with Sky image

ORDER CODES

Micro Prism Optic	HF Gear	3 hr Emergency
T5 3 x 24W	DCNMH324	DCNMH324EM
Living Louvre Optic	HF Gear	3 hr Emergency
T5 3 x 24W	DCNVH324	DCNVH324EM

Options

DALI DIMMING	Replace H with Y in order code	i.e. DCNMY324
DSI DIMMING	Replace H with D in order code	i.e. DCNMD324
SWITCH DIMMING	Replace H with X in order code	i.e. DCNMX324
EASYTEST	Add suffix /ET to order code	i.e. DCNMH324/ ET
COMET	Add suffix /CT to order code	i.e. DCNMH324/ CT

Image Options

SKY	Add suffix /PA to order code	i.e. DCNMH324/ PA
-----	-------------------------------------	--------------------------

Alternative images: Replace PA with PB, FA, FB, FC or FD depending on picture required

Note: Inclusion of an image can reduce light output by up to 25%


duo[®] consult

IP40 dedicated consulting room luminaire

> weblink > **DUOCT**

PRINTED IMAGES


Sky




Autumn



Ladybirds




Shapes



Butterflies



Planets



CEILING INTEGRATION

Refer to common ceiling compatibility matrix – See page 310

Exposed T Grids

T15/T25 Pull up

Spring T Grids

SAS – 150/120

Armstrong – Orcal 1800/3000

Burgess – Clip in/Abar


Plasterboard

Prepared aperture

LAMP PERFORMANCE


Wattage	IL@25°C	Lamp Life
1 x 24W T5	1750	24,000hrs

DIMENSIONS



L	W	H	L ₁	W ₁	KG	KG
598	598	100	536	536	5.9	6.9

PHOTOMETRIC PERFORMANCE



3 x 24W T5
Living Louvre
• LOR = 59.3%
• SHR MAX = 1.85

Utilisation Factors UF(F)

Room Reflectance			Room Index		
C	W	F	1.00	3.00	5.00
0.70	0.50	0.20	0.47	0.60	0.64

TO SPECIFY

Consulting room T5 luminaire with IP40 easy clean front diffuser and living louvre, micro prism controller or picture options to add feature – as Whitecroft Lighting DUO CONSULT