

dusk

Exterior: 2D Security lighting bulkhead



APPLICATION

Areas requiring a value for money IP65 outdoor luminaire including:

- Emergency exit doors (exterior)
- Stairwells
- Walkways
- Amenity areas
- Canopies


SPECIFICATION

- Square or circular polycarbonate body finished Black or White
- Lamp supplied 28W 2D T5
- IP65 ingress protection
- High frequency or switch-start gear
- Mains or 3 hour maintained integral emergency
- Opal or clear prismatic polycarbonate diffuser
- Diffuser fixed to gasketed body with stainless steel fixing screws


PHOTOMETRY

Dusk Round

SURFACE CIRCULAR 2D BULKHEAD - PRISMATIC
1 x 28W 2D T5 Lamp



- LOR = 67%
- SHR MAX = 1.74




UTILISATION FACTORS UF(F)
Room Reflectance Room Index

C	W	F	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.34	0.39	0.44	0.47	0.52	0.55	0.58	0.61	0.63
0.50	0.30	0.20	0.27	0.32	0.36	0.40	0.44	0.48	0.50	0.53	0.56
0.00	0.00	0.00	0.20	0.24	0.28	0.30	0.34	0.37	0.39	0.42	0.44


SHR NOM=1.50

Dusk Square

SURFACE CIRCULAR 2D BULKHEAD - OPAL
1 x 28W 2D T5 Lamp



- LOR = 56.6%
- SHR MAX = 1.71




UTILISATION FACTORS UF(F)
Room Reflectance Room Index

C	W	F	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.29	0.34	0.38	0.41	0.45	0.47	0.50	0.52	0.54
0.50	0.30	0.20	0.24	0.28	0.32	0.34	0.38	0.41	0.43	0.46	0.48
0.00	0.00	0.00	0.18	0.21	0.25	0.27	0.31	0.33	0.35	0.37	0.39

SHR NOM=1.50


DIMENSIONS




300 Ø



85



246 □



82

ORDER CODES - DUSK

2D MAINS AND EMERGENCY RANGE

LAMP SUPPLIED	DIFFUSER/GEAR/BODY COLOUR/MODE	ROUND BODY	SQUARE BODY
1 x 28W 2D T5	Opal/SS/White/Mains	DKROS28W	DKSOS28W
1 x 28W 2D T5	Opal/HF/White/Mains	DKROH28W	DKSOH28W
1 x 28W 2D T5	Prismatic/SS/White/Mains	DKRPS28W	DKSPS28W
1 x 28W 2D T5	Prismatic/HF/White/Mains	DKRPH28W	DKSPH28W
1 x 28W 2D T5	Opal/HF/White/Maintained Em	DKROH28WEMIN	DKSOH28WEMIN
1 x 28W 2D T5	Prismatic/HF/White/Maintained Em	DKRPH28WEMIN	DKSPH28WEMIN

COLOUR Substitute **B** for W in part code

B Black base, i.e. **DKSOS28B**

To specify state:

Surface mounted IP65 bulkhead supplied with a 28W 2D T5 lamp. Square or Round polycarbonate body, colour options Black or White and diffuser options opal or clear prismatic. Gear options high frequency or switch-start with mains or 3 hour maintained integral emergency. Diffuser to be fixed to gasketed body with stainless steel fixing screws – as Whitecroft Lighting DUSK

QuickLink

DSK

Go