

egress recessed

recessed emergency luminaire

> weblink > **EGRN**

Optics

- Lamp options:
 - 1 x 8W T5
- Normal lamp output 400 lumens
- Emergency lamp output 100 lumens

Body

- Fully recessed high grade polycarbonate body mounted in ceiling tile with winged fixings adjustable from below with white lip trim, recess depth 70mm
- 3 hour maintained, non-maintained or mains voltage versions
- High temperature Ni-Cd battery with constant current charger and LED charge indicator
- Cable entry locations at rear
- Ambient 0 – 25°C
- Input voltage 230/240V – 50Hz
- Circuit Watts 8W (non-maintained), 20W (maintained) and 12W (mains)



ORDER CODES


Egress Recessed		3 hr Emergency
T5 1 x 8W	3 hour non-maintained	EGRXNMF8
T5 1 x 8W	3 hour maintained	EGRXMF8
T5 1 x 8W	mains voltage	EGRXF8

Options

EASYTEST Add suffix **/ET** to order code i.e. EGRXNMF8/**ET**

Note: Available with COMET. Please refer to our sales office for details

DIMENSIONS



L	W	H	KG
420	172	83	1.5

TO SPECIFY

Fully recessed 8W T5 IP20 emergency luminaire in 3 hour self contained maintained, non-maintained or mains voltage versions. Polycarbonate body recess <70mm mounted in ceiling tile with winged fixings. High temperature Ni-Cd battery with constant current charger and LED charge indicator – as Whitecroft Lighting EGRESS RECESSED