

Optics

- Lamp options:
 - 20W CDM-TM
 - 35W CDM-TC
 - 70W CDM-T
- Specular anodized aluminium reflector with rectangular facets

Body

- Electronic control gear
- Universal 3 phase adapter included for use with 3 circuit track or 12 circuit "iTrack"
- Ballast housing and luminaire housing of enamelled aluminium extrusion / die cast aluminium painted White or Black
- Swivels 360° and tilts 0-90°



Order Codes

Spot Reflector

20W CDM-TM	White	EMPH-C20E-M3-21
35W CDM-TC	White	EMPH-C35E-M3-21
70W CDM-T	White	EMPH-C70E-M3-21

Medium Reflector

20W CDM-TM	White	EMPH-C20E-M3-22
35W CDM-TC	White	EMPH-C35E-M3-22
70W CDM-T	White	EMPH-C70E-M3-22


Flood Reflector

20W CDM-TM	White	EMPH-C20E-M3-23
35W CDM-TC	White	EMPH-C35E-M3-23
70W CDM-T	White	EMPH-C70E-M3-23

Options

BLACK	Replace 1st Number 2 with 3	i.e. EMPH-C70E-M3-31
-------	-----------------------------	----------------------

Dimensions



Version	L	W	H	KG
20/35W	125	131	141	1.0
70W	159	171	194	1.3

Photometric Performance

70W Spot			70W Medium			70W Flood		
MH	LUX	Ø	MH	LUX	Ø	MH	LUX	Ø
1.0m	45802	0.3	1.0m	19748	0.4	1.0m	12072	0.6
2.0m	11451	0.5	2.0m	4937	0.9	2.0m	3018	1.2
3.0m	5089	0.8	3.0m	2194	1.3	3.0m	1341	1.8
4.0m	2883	1.0	4.0m	1234	1.8	4.0m	755	2.4
5.0m	1832	1.3	5.0m	790	2.2	5.0m	483	3.1

To Specify

Track mounted spotlight for 20W CDM-TM, 35W CDM-TC or 70W CDM-T lamp with integral electronic gear. Die cast aluminium body which swivels 360° and tilts 0-90°. Specular anodized aluminium reflector with rectangular facets – as Whitecroft Lighting EMPHASIS