



Optics

- 3000K or 4000K options
- 17° or 54° beam angles
- 9.5W total power consumption (inc. driver)
- Total power consumption will decrease as LED technology advances
- High quality single bin LEDs
- Lower point brightness due to the unique LED arrangement
- 50,000 hours life expectancy

Body

- For use with iTrack or 3 circuit track
- Extruded aluminium luminaire housing and body painted white or black
- Swivels 360° and tilts 0-90°

Driver


- Constant Current 350mA

Order Codes

Spot Beam (17°)		
3000K	White	EMPH3KSPW
4000K	White	EMPH4KSPW
Medium Beam (54°)		
3000K	White	EMPH3KFLW
4000K	White	EMPH4KFLW
Options		
BLACK FINISH	Replace W with BK	i.e. EMPH4KFL BK



Dimensions



W	L	H	KG
110	109	160	1.2

Photometric Performance

54° 4000K			17° 4000K		
MH	LUX	Ø	MH	LUX	Ø
1.0m	519	1.1	1.0m	4726	0.3
2.0m	130	2.2	2.0m	1182	0.5
3.0m	58	3.4	3.0m	525	0.8
4.0m	32	4.5	4.0m	295	1.1
5.0m	21	5.6	5.0m	189	1.4

To Specify

Track mounted LED spotlight with integrated driver. Extruded aluminium luminaire housing and body providing spot (17°), medium (54°) distribution with 360° swivel and tilts 0-90° – as Whitecroft Lighting EMPHASIS LED