

Esprit EX

compact fluorescent
downlighter



Optics

- Lamp options:
 - 1 or 2 x 26W TC-D
- Anodised plain reflector

Body

- Cast aluminium body with cast aluminium bezel painted white
- 3 point fixing for ceilings, 1mm to 25mm thick
- Supplied with cut aperture support ring to simplify installation
- Integrated removable gear tray




Order Codes

Esprit EX	HF Gear	3 hr Emergency
TC-D 1 x 26W	EXH126P	EXH126PEM
TC-D 2 x 26W	EXH226P	EXH226PEM

Attachment

IP44 clear disc	EXA-IP44C
-----------------	-----------


Dimensions



L	W	H	CAØ	KG	KG
420	240	171	230 ⁺¹	2.0	3.0

Performance Guide

Lamps	Illuminance	Spacing
2 x 26W TC-D	210 lux	3.0m x 3.0m




Maintenance:
0.8
Reflectance:
70/50/20
Ceiling Height:
2.7m
Working Plane:
0.0m

Lamp Performance

Wattage	IL@25°C	Lamp Life
1 x 26W TC-D	1800	13,000hrs

Photometric Performance



2 x 26W TC-D
Plain Reflector
• LOR = 66.1%
• SHR MAX = 1.68

Utilisation Factors UF(F)

Room Reflectance	Room Index
C W F	1.00 3.00 5.00
0.70 0.50 0.20	0.46 0.61 0.65

To Specify

Compact fluorescent downlighter with cast aluminium body, white cast aluminium bezel, integral control gear and plain silver reflector – as Whitecroft Lighting ESPRIT EX