

esprit MRI

downlighter for MRI scanning rooms

> weblink > **EMRI**

Optics

- Anodised aluminium reflector
- 75W Osram Halolux E27 base tungsten halogen lamp included

Body

- One piece assembly with precision moulded bezel
- Only non-ferrous materials are used in the construction
- User friendly rapid fix push down straps with 3 point location




ORDER CODES

Esprit MRI	Standard
TH 1 x 75W	ESTH75

PERFORMANCE GUIDE

Lamps	Illuminance	Spacing
1 x 75W TH	360 lux	1.8m x 1.2m




Maintenance:
0.8
Reflectance:
70/50/20
Ceiling Height:
2.7m
Working Plane:
0.8m

LAMP PERFORMANCE


Wattage	IL@25°C	Lamp Life
1 x 75W TH	1100	2,000hrs

DIMENSIONS



L	W	H	CAØ	KG
363	218	114	200	0.9

PHOTOMETRIC PERFORMANCE



Utilisation Factors UF(F)

Room Reflectance			Room Index		
C	W	F	1.00	3.00	5.00
0.70	0.50	0.20	0.59	0.84	0.89

TO SPECIFY

One piece compact recessed downlighter for MRI scanning rooms, fabricated from non-ferrous materials and containing no electronic gear – as Whitecroft Lighting ESPRIT MRI