

euroflood midi

> weblink > **MIDI**

Optics

- Lamp options:
 - 250W SON-T/HQI-T
 - 400W SON-T/HQI-T
- Asymmetric light distribution for low light pollution
- Precise asymmetric optical control

Body

- IP65
- Precision diecast aluminium
- Polyester powder coat finished in black or white
- Hammered, high-grade aluminium reflector, brightened and anodised
- Toughened glass
- Mounting by cradle supplied
- Attachments:
 - Uplighter bracket (interior applications)
 - Wire guard
 - Glare louver
 - Glare baffle
- Takes supply cable of 5-10mm diameter




ORDER CODES

Euroflood Midi (Black)	
SON-T 250W	SC250S
SON-T 400W	SC400S
HQI-T 250W	SC250H
HQI-T 400W	SC400H

Options

WHITE	Add suffix /W to order code	i.e. SC250S/W
WIRE GUARD		SCWG250400R08
GLARE BAFFLE		SCGS250400R08
GLARE LOUVRE		SCGL250400R08
UPLIGHTER BRACKET BLACK		SCUBMD
UPLIGHTER BRACKET WHITE		SCUBMD/W

PHOTOMETRIC PERFORMANCE



WINDAGE


VERSION	WATTAGE	WINDAGE*
SC250	250W	0.08m ²
SC400	400W	0.08m ²

*Figures are given for the typical mounting position i.e. side windage

LAMP PERFORMANCE

Wattage	IL@25°C	Lamp Life
250W HQI-T	20000	9,000hrs
250W SON-T	28000	24,000hrs
400W HQI-T	32000	9,000hrs
400W SON-T	48000	24,000hrs

DIMENSIONS



Version	L	W	H	KG
SC250	435	180	460	12.5
SC400	435	180	460	14.0

TO SPECIFY

Die cast aluminium precision floodlight with asymmetric beam and toughened glass lens. Sealed to IP65 – as Whitecroft Lighting EUROFLOOD MIDI