



Optics

- Lamp options:
 - 70W HQI-TS/CDM-TD
 - 150W HQI-TS/CDM-TD
 - 300W Tungsten Halogen
- Asymmetric light distribution for low light pollution
- Precise asymmetric optical control
- Hammered, high-grade aluminium reflector, brightened and anodised
- Toughened glass

Body

- IP65
- Precision diecast aluminium low profile design
- Polyester powder coat finished in black or white
- Mounting by cradle supplied
- Accessories:
 - Uplighter bracket (interior applications)
- Takes supply cable of 5-10mm diameter
- Timed ignitor
- Can be used in uplight or downlight orientation





Sainsbury's

CYCLE
PARKING
←

play
here!

euroflood mini

Order Codes

Euroflood Mini (Black)

HQI-TS/CDM-TD 70W

SC70/B

HQI-TS/CDM-TD 150W

SC150/B

TUNGSTEN HALOGEN 300W

SC300/B

Options

WHITE Replace B with W

i.e. SC70/W

UPLIGHTER BRACKET BLACK

SCUBMN

UPLIGHTER BRACKET WHITE

SCUBMN/W




Windage

Version	Wattage	Windage*
SC70	70W	0.03m ²
SC150	150W	0.03m ²

*Figures are given for the typical mounting position i.e. side windage

Dimensions




Version	L	W	H	KG
SC70	235	88	350	6.0
SC150	235	88	350	6.5



White




Uplighter Bracket



Uplighter Bracket

Photometric Performance



1 x 70W
CDM-TD/HQI-TS
• LOR = 68%

Lamp Performance

Wattage	IL@25°C	Lamp Life
70W CDM-TD	6000	16,000hrs
70W HQI-TS	7500	6,000hrs
150W CDM-TD	14200	16,000hrs
150W HQI-TS	12000	12,000hrs
300W TH	7000	1,000hrs

To Specify

Die cast aluminium precision floodlight with asymmetric beam. Body <89mm deep 70/150W HQI-TS/CDM-TD lamp. IP65 – as Whitecroft Lighting EUROFLOOD MINI